

Web Sensor with PoE - one channel remote thermometer hygrometer





One channel p-line Web Sensor with PoE. Temperature or humidity + temperature probe is supported. Remote alarm.

Processing and analysis of measured data:

- online in **COMET Cloud**
- <u>COMET Database</u> software
- integration into 3-party systems

Technical data

reciliicai uata	
TEMPERATURE SENSOR	
Measuring range	-55 to +105 °C
Accuracy	according to the connected probe DSxx
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	according to the connected probe DSxx
Accuracy	according to the connected probe DSxx
Resolution	0.1% RH
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	1x external temperature probe nebo 1x connectable temperature+humidity probe
Output	Ethernet
Measuring interval	2 s
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	Power over Ethernet according to IEEE 802.3af or 5Vdc
Protection class	IP30
Dimensions	88 x 74 x 39,5 mm
Weight	approx. 125 g
Warranty	3 years