# XZCP11V12L2

Pre wired connectors XZ, straight female, M12, 5 pins, cable PUR 2 m



Main		
Range of Product	Telemecanique Cabling components	
Accessory / separate part category	Cabling accessory	
Accessory / Separate Part Type	Pre-wired connectors	
Series name	General purpose	

Complementary

o compromornary		
Electrical connection	Straight female connector M12, 5 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	6.56 ft (2 m)	
Cable outer diameter	0.22 in (5.7 mm)	
Cable composition	5 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	250 V AC 300 V DC	
Line Rated Current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	

#### **Environment**

IP Degree of Protection	IP65 IP67 IP69K	
Product Certifications	cULus	
Ambient air temperature for operation	-40176 °F (-4080 °C) static 23176 °F (-580 °C) flexing	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	-

### Ordering and shipping details

Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	00785901029441	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	
Returnability	No	
Country of origin	CZ	

## Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	7.09 in (18 cm)
Package 1 Length	7.28 in (18.5 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Weight	4.39 lb(US) (1.99 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	<sup>™</sup> REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	₫Yes	