

Electronic housing - BC 107,6 DEV-KIT KMGY - 2202525

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



DEV-KIT BC 107,6: contains 1 x BC 107,6 housing and PCB terminal blocks (MKDS), supplied in individual parts

Your advantages

- Standard-compliant housing according to DIN 43880 with overall width of 107,6 mm
- PCB terminal blocks with 5 mm pitch, conductor cross section 1.5 mm²
- ☑ Optional perfboard for soldering THT components by hand
- ☑ Connection of individual housing modules with each other by means of the optional HBUS via DIN rail

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	4 055626 141756
GTIN	4055626141756

Technical data

General

Housing type	Component housing
Housing material	Polycarbonate
Color (RAL)	light gray

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	89.7 mm
Height	62.2 mm
Width	107.6 mm
Standards and Regulations	

Flammability rating according to UL 94	VO
--	----



Electronic housing - BC 107,6 DEV-KIT KMGY - 2202525

Technical data

Environmental Product Compliance

		Lead 7439-92-1		
China RoHS		Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to Category "Manufacturer's declaration"		tab "Downloads",	
Approvals				
Approvals				
pprovals				
JL Recognized / EAC				
x Approvals				
Approval details				
UL Recognized	91	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868	
EAC	EAC		B.01742	

Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com