





## Metric table

Ų							Dimensions ir	n: millimeters - <i>inch</i>
<b>I</b> <sub>1</sub> ±0.25	<b>d</b> Thread	а	b <sub>1</sub>	b <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	<b>I</b> <sub>2</sub> ±0.2	t min.
110	M 6	10	9.5	33	32	24	90	9
<i>4.33</i>		<i>0.39</i>	<i>0.37</i>	<i>1.30</i>	1.26	0.94	<i>3.54</i>	<i>0.35</i>
125	M 6	10	9.5	33	32	24	105	9
4.92		<i>0.39</i>	<i>0.37</i>	<i>1.30</i>	1.26	0.94	<i>4.13</i>	<i>0.35</i>
140	M 6	10	9.5	33	32	24	120	9
5.51		0.39	0.37	<i>1.30</i>	1.26	0.94	4.72	0.35

# Specification

### Aluminum

- Powder coated
  Black, RAL 9005, textured finish
- Silver, RAL 9006, textured finish
- Anodized finish, natural color
- Plain, tumbled finish

RoHS compliant

#### On request

Special lengths

Various metric size fasteners and kit packaging

## Information

2

• sw

SR

€EL

OBL

GN 730 ledge handles are used on doors, guards and hatches on machines, as well as on drawers and pull-out units. They are attached from the back side via the mounting threads.

For certain minimum quantities special lengths can also be easily produced.

#### see also ...

- Ledge Handles GN 430 / GN 430.1 (Aluminum) → page 188
- Ledge Handles EN 130 (Technopolymer Plastic) → www.jwwinco.com

How to order GN 730-125-SW		Length I <sub>1</sub>
		Finish