



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

MJE4343 (NPN) & MJE4353 (PNP) Silicon Complementary Transistors High Voltage Power Amplifier TO-3PN Type Package

Description:

The MJE4343 (NPN) and MJE4353 (PNP) are silicon complementary transistors in a TO-3PN type package designed for use in high power audio amplifier applications and high voltage switching regulator circuits.

Features:

- High Collector-Emitter Sustaining Voltage: $V_{CEO(sus)} = 160V$
- High DC Current Gain: $h_{FE} = 35$ Typ @ $I_C = 8A$
- Low Collector-Emitter Saturation Voltage: $V_{CE(sat)} = 2V$ Max @ $I_C = 8A$

Absolute Maximum Ratings:

Collector-Emitter Voltage, V_{CEO}	160V
Collector-Base Voltage, V_{CB}	160V
Emitter-Base Voltage, V_{EB}	70V
Collector Current, I_C	
Continuous	16A
Peak (Note 1)	20A
Continuous Base Current, I_B	5A
Power Dissipation ($T_C = +25^\circ C$), P_D	125W
Operating Junction Temperature Range, T_J	-65° to +150°C
Storage Temperature Range, T_{stg}	-65° to +150°C
Thermal Resistance, Junction-to-Case, R_{thJC}	1°C/W

Note 1. Pulse Test: Pulse Width $\leq 5ms$, Duty Cycle $\geq 10\%$.

Electrical Characteristics: ($T_C = +25^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 200mA$, $I_B = 0$, Note 2	160	-	-	V
Collector-Emitter Cutoff Current	I_{CEX}	$V_{CE} = 160V$, $V_{EB(off)} = 1.5V$	-	-	0.1	mA
		$V_{CE} = 160V$, $V_{EB9off)} = 1.5V$, $T_C = +150^\circ C$	-	-	5.0	mA
	I_{CEO}	$V_{CE} = 80V$, $I_B = 0$	-	-	750	μA
Emitter-Base Cutoff Current	I_{EBO}	$V_{BE} = 7V$, $I_C = 0$	-	-	1.0	mA
Collector-Base Cutoff Current	I_{CBO}	$V_{CB} = 160V$, $I_E = 0$	-	-	750	μA

Note 2. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\geq 2\%$.

Electrical Characteristics (Cont'd): ($T_C = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
ON Characteristics (Note 2)						
DC Current Gain	h_{FE}	$V_{CE} = 2\text{V}, I_C = 8\text{A}$	15	35	-	
		$V_{CE} = 4\text{V}, I_C = 16\text{A}$	8	15	-	
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C = 8\text{A}, I_B = 0.8\text{A}$	-	-	2.0	V
		$I_C = 16\text{A}, I_B = 2\text{A}$	-	-	3.5	V
Base-Emitter Saturation Voltage	$V_{BE(\text{sat})}$	$I_C = 16\text{A}, I_B = 2\text{A}$	-	-	3.9	V
Base-Emitter ON Voltage	$V_{BE(\text{on})}$	$V_{CE} = 4\text{V}, I_C = 16\text{A}$	-	-	3.9	V
Dynamic Characteristics						
Current-Gain Bandwidth Product	f_T	$V_{CE} = 20\text{V}, I_C = 1\text{A}, f = 0.5\text{MHz}$, Note 3	1.0	-	-	MHz
Output Capacitance	C_{ob}	$V_{CB} = 10\text{V}, I_E = 0, f = 0.1\text{MHz}$	-	-	800	pF

Note 2. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\geq 2\%$.

Note 3. $f_T = |h_{FE}| \cdot f_{\text{test}}$.

