## SIEMENS

## Data sheet

product type designation

## 6GK5750-2HX01-1AB0

SIEME	NS	

## W1750D-2IA RJ45 Direct AP (USA)

transfer rate			
transfer rate			
with WLAN / maximum	2500 Mbit/s		
<ul> <li>with WLAN / in the 2,4 GHz frequency band / maximum</li> </ul>	800 Mbit/s		
<ul> <li>with WLAN / in the 5 GHz frequency band / maximum</li> </ul>	1733 Mbit/s		
for Industrial Ethernet	10, 100, 1000 Mbit/s		
transfer rate / for Industrial Ethernet			
• minimum	10 Mbit/s		
• maximum	2000 Mbit/s		
transfer rate / note	Max. transmission rate each for aggregation		
interfaces			
number of electrical/optical connections / for gigabit Ethernet / maximum	2		
number of electrical connections			
<ul> <li>for network components or terminal equipment</li> </ul>	2		
<ul> <li>for power supply</li> </ul>	1		
<ul> <li>for redundant voltage supply</li> </ul>	0		
number of interfaces / according to USB	1		
type of electrical connection			
<ul> <li>for network components or terminal equipment</li> </ul>	RJ45 socket		
<ul> <li>for power supply</li> </ul>	DC plug 2.1/5.5-mm (2.1/5.5-mm center-positive circular plug with 9.5 mm length)		
<ul> <li>of the USB interface</li> </ul>	USB2.0 Type A		
interfaces / wireless			
number of radio cards / permanently installed	2		
transmission mode / for multiple input multiple output (MIMO)	4x4; 4 spatial streams SU-MIMO for up to 1733 Mbps - 3 spatial streams MU-MIMO for up to 1300 Mbps		
number of spatial streams	4		
number of internal antennas	8		
antenna gain compared to spherical radiator / of the WLAN antenna			
<ul> <li>in the 2.4 GHz frequency band</li> </ul>	3.5 dB		
• in the 5 GHz frequency band	5 dB		
supply voltage, current consumption, power loss			
type of voltage / of the supply voltage	DC		
supply voltage			
<ul> <li>from Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af</li> </ul>	48 V		

<ul> <li>from Power-over-Ethernet according to IEEE802.3at</li> </ul>	48 V
for type 2	
ambient conditions	
ambient temperature	
during operation	0 50 °C
during storage	-40 +70 °C
relative humidity / at 25 °C / without condensation / during	93 %
operation / maximum	
protection class IP	IP20
design, dimensions and weights	
width	210 mm
height	210 mm
depth	57 mm
width / of the enclosure / without antenna	210 mm
height / of the enclosure / without antenna	210 mm
depth / of the enclosure / without antenna	57 mm
net weight	0.95 kg
fastening method	Ceiling mounting
wall mounting	No
radio frequencies	
operating frequency	
<ul> <li>for WLAN in 2.4 GHz frequency band</li> </ul>	2.4 2.48 GHz; depending on the country approvals
<ul> <li>for WLAN in 5 GHz frequency band</li> </ul>	5.15 5.85 GHz; depending on the country approvals
product features, product functions, product components	/ general
product function / Access Point Mode	Yes
product function / client Mode	No
number of SSIDs	16
product function	
• dual client	No
product functions / management, configuration, engineeri	ng
product function	
• CLI	Yes
<ul> <li>web-based management</li> </ul>	Yes
<ul> <li>operation with IWLAN controller</li> </ul>	No
<ul> <li>operation with Enterasys WLAN controller</li> </ul>	No
<ul> <li>operation with Aruba Mobility Controllers</li> </ul>	Yes
product functions / Direct Access Point	
number supported Direct Access Point	128
operating mode / as Direct Access Point	Yes
product functions / DHCP	
product function	
DHCP client	Yes
standards, specifications, approvals	
standard	
<ul> <li>for safety / from CSA and UL</li> </ul>	UL/IEC/EN 60950
certificate of suitability	
<ul> <li>EC Declaration of Conformity</li> </ul>	Yes
CE marking	Yes
• C-Tick	Yes
<ul> <li>E1 approval</li> </ul>	No
<ul> <li>Power-over-Ethernet according to IEEE802.3at for</li> </ul>	Yes
type 2	
standard for wireless communication	Vee
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes

	_
wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
further information / internet-Links	www.sichens.dentilitzuldssungen
Internet-Link	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	http://www.siemens.com/tia-selection-tool
<ul> <li>to the website: IWLAN</li> </ul>	http://www.siemens.com/iwlan
<ul> <li>to website: Industry Mall</li> </ul>	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/automation/net/catalog
<ul> <li>to website: Image database</li> </ul>	http://automation.siemens.com/bilddb
<ul> <li>to website: CAx-Download-Manager</li> </ul>	http://www.siemens.com/cax
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

7/1/2021 🖸