




MUS19-10-10-F

Ruland MUS19-10-10-F, 10mm x 10mm Single Universal Joint, Friction Bearing, Steel, 18.9mm OD, 45.0mm Length





Description

Ruland MUS19-10-10-F is a single cardan friction bearing universal joint with 10mm x 10mm bores, 18.9mm OD, and 45.0mm length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. MUS19-10-10-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT12/19-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

10 mm	Small Bore (B2)	10 mm
12.5 mm	B2 Max Shaft Penetration	12.5 mm
18.9 mm	Bore Tolerance	+0.015 mm / -0.000 mm
45.0 mm	Yoke Length (LY)	22.5 mm
12.5 mm	Peak Torque	141.2 Nm
28.2 Nm	Max Operating Angle	45°
Alloy Steel	Manufacturer	Belden Universal
USA	Weight (lbs)	0.149600
LUBRIPLATE No. 1200-2	UPC	634529287620
8483.60.4000	UNSPC	25173810
Performance ratings are for guidance only. The user must determine suitability for a particular application.		
•	. ,	•
	12.5 mm 18.9 mm 45.0 mm 12.5 mm 28.2 Nm Alloy Steel USA LUBRIPLATE No. 1200-2 8483.60.4000 Performance ratings are for guides and California to cause cancer and California to C	12.5 mm 18.9 mm Bore Tolerance 45.0 mm Yoke Length (LY) 12.5 mm Peak Torque 28.2 Nm Max Operating Angle Alloy Steel Manufacturer USA Weight (Ibs) LUBRIPLATE No. 1200-2 8483.60.4000 UNSPC Performance ratings are for guidance only. The user must determine ▲WARNING This product can expose you to the chemical Ethylen California to cause cancer and birth defects or other reproductive has