

## General ordering data

Order No. Part designation Version

## EAN Qty.

## Markings

Cadmium		
Can be labelled with thermal transfer printers		
Can be printed with plotter		
Can be written with dot-matrix printer		
Can be written with laser printer		
Colour of printing		
Function		
Halogen		
Length		
Material		
Material colour		
Material colour according to resistance code		
Max. temperature, continuous		
Min. temperature, continuous		
Orientation of print		
Pin can be written (STI)		
Pitch		
PrintJet		
Printed characters		
Printing method		
Silicone		
Speed marking laser		
Type of printing		
UL 94 flammability class		
Width		

0468260101 DEK 6,5 FS 101-150 Connector markers, L x W: 5 x 6.5 mm, Polyamide, white 4008190049218 500 pc(s).

no
No
No
No
No
black
Connector markers
no
5 mm
Polyamide
white
9
100 °C
-40 °C
vertical
No
6.5 mm
No
Numbers
MC Laser
no
No
Standard
V2
6.5 mm



Classifications	
ETIM 2.0	EC000761
ETIM 3.0	EC000761
eClass 4.1	24-19-02-19
eClass 5.0	27-14-11-37
eClass 5.1	27-14-11-37

## Similar products

Order No.		
0468260001	DEK 6,5 FS 1-50	Connector markers, L x W: 5 x 6.5 mm, Polyamide, white
0468260051	DEK 6,5 FS 51-100	Connector markers, L x W: 5 x 6.5 mm, Polyamide, white



