SIEMENS

Data sheet

6GK5992-2HA00-0AA0

product type designation product description

MM992-2 M12 GIGA

XR-300 media module

SCALANCE X accessory; Media module MM992-2M12; 2x 1000 Mbit/s industrial Ethernet, M12 connection system electrical, Media module, Conformal coating



interfaces	
number of electrical/optical connections / for network	2
components or terminal equipment / maximum	
number of electrical connections	
 for network components or terminal equipment / maximum 	2
number of 10/100/1000 Mbit/s M12 ports	2
type of electrical connection	
 for network components or terminal equipment 	M12
number of 1000 Mbit/s SC ports (SX)	2
ambient conditions	
ambient temperature	
 during operation 	-40 +70 °C
 during storage 	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Media module
width	60 mm
width height	60 mm 22 mm
height	22 mm
height depth	22 mm 100 mm
height depth net weight	22 mm 100 mm 0.08 kg
height depth net weight product feature / conformal coating	22 mm 100 mm 0.08 kg Yes
height depth net weight product feature / conformal coating fastening method	22 mm 100 mm 0.08 kg Yes latched
height depth net weight product feature / conformal coating fastening method • installation in media module slot	22 mm 100 mm 0.08 kg Yes latched
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals	22 mm 100 mm 0.08 kg Yes latched Yes
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals certificate of suitability	22 mm 100 mm 0.08 kg Yes latched Yes EN 61000-6-2:2005, EN 61000-6-4:2007
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals certificate of suitability • CE marking	22 mm 100 mm 0.08 kg Yes latched Yes EN 61000-6-2:2005, EN 61000-6-4:2007 Yes
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals certificate of suitability • CE marking • C-Tick	22 mm 100 mm 0.08 kg Yes latched Yes EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals certificate of suitability • CE marking • C-Tick • KC approval	22 mm 100 mm 0.08 kg Yes latched Yes EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes Yes
height depth net weight product feature / conformal coating fastening method • installation in media module slot standards, specifications, approvals certificate of suitability • CE marking • C-Tick • KC approval • railway application in accordance with EN 50155	22 mm 100 mm 0.08 kg Yes latched Yes EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes Yes Yes Yes

6GK59922HA000AA0 Page 1/2

further information / internet-Links

Internet-Link

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

last modified:

http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

12/15/2020 🖸