

International **IR** Rectifier

THREE PHASE BRIDGE

Features

- Low V_F
- Low profile package
- Direct Mounting to heatsink
- Flat-Pin/ Round-Pin versions with PCB solderable terminals
- Low junction-to-case Thermal Resistance
- 3500 V_{RMS} insulation voltage
- UL approval pending

Applications: Power conversion machines

- Welding
- UPS
- SMPS
- Motor Drives
- General Purpose & Heavy Duty Applications

Description

A range of extremely compact three-phase rectifier bridges offering efficient and reliable operation.

The low profile package has been specifically conceived to maximize space saving and optimize the electrical layout of the application specific Power Supplies.




Major Ratings and Characteristics

Parameters	40MT	70MT	100MT	Units
I_o	45	75	100	A
@ T_c	100	80	80	°C
I_{FSM} @ 50Hz	270	380	450	A
@ 60Hz	280	398	470	
I^2t @ 50Hz	365	724	1013	A^2s
@ 60Hz	325	660	920	
$I^2\sqrt{t}$	3650	7240	10130	$A^2\sqrt{s}$
V_{RRM}	1400 & 1600			V
T_{STG} range	-40 to 125			°C
T_j range	-40 to 150			

MTP 3-Phase Rectifier Series

Power Module

45 A
75 A
100 A



MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code reverse voltage V	V_{RRM} , maximum repetitive peak reverse voltage V	V_{RSM} , maximum non-repetitive peak V	I_{RRM} max. $@ T_J = 150^\circ C$ mA
40-70-100MT140P	140	1400	1500	5
40-70-100MT160P	160	1600	1700	

Forward Conduction

Parameter	40MT	70MT	100MT	Units	Conditions								
I_o Maximum DC output current @ Case temperature	45	75	100	A	120° Rect conduction angle								
	100	80	80	°C									
I_{FSM} Maximum peak, one-cycle forward, non-repetitive on state surge current	270	380	450	A	t = 10ms	No voltage reapplied	Initial $T_J = T_J \text{ max.}$						
	280	398	470		t = 8.3ms	100% V_{RRM} reapplied							
	225	320	380		t = 10ms								
	240	335	400		t = 8.3ms								
I^2t Maximum I^2t for fusing	365	724	1013	A ² s	t = 10ms	No voltage reapplied							
	325	660	920		t = 8.3ms	100% V_{RRM} reapplied							
	253	512	600		t = 10ms								
	240	467	665		t = 8.3ms								
$I^2\sqrt{t}$	3650	7240	10130	A ² \sqrt{s}	t = 0.1 to 10ms, no voltage reapplied								
V_{FTO}	0.78	0.82	0.75	V	@ T_J max.								
r_t	14.8	9.5	8.1	mΩ									
V_{FM}	1.45 $I_{pk} = 40A$	1.45 $I_{pk} = 70A$	1.51 $I_{pk} = 100A$	V	$T_J = 25^\circ C$ $t_p = 400\mu s$ single junction								

Insulation Table

Parameter	40MT	70MT	100MT	Units	Conditions	
V_{INS}	RMS insulation voltage	3500		V	$T_J = 25^\circ C$ all terminal shorted $f = 50Hz, t = 1s$	

Thermal and Mechanical Specifications

Parameter	40MT	70MT	100MT	Units	Conditions
T _J Maximum junction operating temperature range	- 40 to 150			°C	
T _{stg} Maximum storage temperature range	-40 to 125			°C	
R _{thJC} Maximum thermal resistance, junction to case	0.27	0.23	0.19	K/W	DC operation per module
	1.6	1.38	1.14		DC operation per junction
	0.38	0.29	0.22		120° Rect conduction angle per module
	2.25	1.76	1.29		120° Rect conduction angle per junction
R _{thCS} Maximum thermal resistance, case to heatsink	0.1			K/W	Per module. Mounting surface smooth, flat and greased. Heatsink compound thermal conductivity = 0.42W/mk
T Mounting torque ± 10% to heatsink	4			Nm	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound.
wt Approximate weight	65			g	Lubricated threads.

Clearance and Creepage Distances

Parameter	MT...PA	MT...PB	Units
Clearance (external shortest distance in air between terminals which are not internally short circuited together)	10.9	12.3	mm
Creepage distance (shortest distance along external surface of the insulating material between terminals which are not internally short circuited together)	10.9	12.3	mm

Ordering Information Table



Device Code	10 0 MT 160 P B
1	- Current rating code
2	- Circuit configuration code: 0 = 3-Phase Rectifier Bridge
3	- Essential part number
4	- Voltage code: code x 10 = V _{RRM} (See Voltage Ratings table)
5	- Pinout code:
	4 = 45A 7 = 75A 10 = 100A
	A = Flat pins B = Round pins






MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IR Rectifier

Outline Table





MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IR Rectifier




Fig. 6 - Current Rating Characteristics




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Maximum Non-Repetitive Surge Current




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 10 - Current Rating Nomogram (1 Module Per Heatsink)




Fig. 11 - Current Rating Characteristics




Fig. 12 - On-state Voltage Drop Characteristics




Fig. 13 - Maximum Non-Repetitive Surge Current




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Current Rating Nomogram (1 Module Per Heatsink)

MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IR Rectifier




Fig. 16 - Thermal Impedance Z_{thJC} Characteristics

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 06/02