SPE	CIFICATION CONTROL DRAWING		55A6455
Title	WIRE, RADIATION-CROSSLINKED, MODIFIED ETFE-INSULATED, NORMAL WEIGHT, GENERAL PURPOSE, 600 VOLT	Date 11-30-05	Revision C
	This specification sheet forms a part of the latest issue of Raychem Spe	cification 55A.	
CONDU	JCTOR – TIN-COATED COPPER NOTE: Controlled Free Tin-Coating		
	Thickness – 40 micro inches (minimum)		
		$\backslash$	
	ADDITIONAL REQUIREMENTS		
so	DLDERABILITY (Quality Conformance): 95% (minimum) coverage per MIL-STD-202, Me	ethod 208 (1 hour s	steam aging)
	ccept as specified above, this construction shall meet all the requirements of Raychem S AWG sizes 24 through 10.	Specification Sheet	55A0811
	ART NUMBER:		
	e 55A6455 part number shall be modified to include the applicable AWG size followed b	by a color code des	signator.
<u>1</u> /	Example: AWG 20, white: 55A6455-20-9		
-	Users should evaluate the suitability of this product for their application. Specifications are sub also reserves the right to make changes in materials or processing, which do not affect compliance		
SUFFIXES MAY	COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS HE PURCHASE ORDER.		<b>Raychem Wire &amp; Cable</b> 501 Oakside Avenue
Page 1 of 1	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL.	Electronics	Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.		