AR12105FSC



Finland:

Denmark:

Sweden:

•

•

•



Sample image

Height

Dimensions:

Temperature °F (continuous):

Order symbol: AR12105FSC EAN: 6418074098627 Product nbr: 8561689 El. number: Description: PC Enclosure Remarks: Opaque flat screw cover

Including: Flat screw cover. Base with 10-32 brass inserts, cover with formed in place PUR gasket and 4 stainless cover screws. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting

	noight		Doptil		1000
mm:	305	254	127		ASPH
inch:	12	10	5		ALBP:
					ASP1
Materials:					ACDI
Material:	Polycart	Polycarbonate			ASPK
Base colour:	RAL 703	85 -light grey	ý		ADFP
Cover colour:	RAL 703	RAL 7035 -light grey			APBP
Gasket material:	Polyuret	hane			
					AMFL
					ABP1
Temperatures:					
Temperature °C (short	term)::		40 140		
Temperature °C (contin	uous):	-4	40 80		Ratin
Temperature °F (short t	erm):		40 250		Ingre

Width

Depth

-40 ... 175

Accessories:						
ASPHK12	Swing Panel Kit w/o Panel					
ALBP1210	Aluminum Back Panel (274 x 226)					
ASP1210	Aluminum Swing Panel (254.5 x 305.7 x 0)					
ASPK1210	Swing Panel Kit incl. Panel					
ADFP1210	Dead Front Panel w/ screws (257.5 x 307.5 x 0)					
APBP1210	PVC Back Panel (274 x 226)					
AMFL10	10" Mounting Flange Set					
ABP1210	Painted Steel Back Panel (274 x 226)					

ng:

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK09;
Electrical insulation:	Not insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 508
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	NEMA 4, 4X, 6, 6P, 12, 12K and 13

Certificates:

 \circledast Fibox Oy, Data subject to change without notice (printed: 20.07.2022)