

Wiha Quality Tools Germany

www.wihatools.com



Wiha Precision ESD Safe Chip Lifter



handle high quality plastic, Dissipative material.										
Item	mm	mm	mm	mm	Inch	lbs.	pkg.			
No.	1	3.5	50	145	5.7	.07	1			
279 20	ESD	ESD Safe dissipative handle								



/		
•	D	

ESD standard IEC 61340-5-1

SHOP

920 92 Master Technicians Bench Top Set

Plexiglass frame. Equipped with 50 precision ESD Safe screwdrivers. Item No. 920 92 Slotted: .8, 1.0, 1.2, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0mm Phillips: #000, #00, #0, #1 Torx: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T15, T20 lbs. 2.25 Metric Hex: .7, .9, 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm Inch Hex: 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32" Metric Nut Drivers: 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5mm 279 20 Chip Lifter



911 18 Rugged Polyester Canvas Storage Pouch Holds 8 Precision Tools up to 170mm in length. Folding pouch. Has security flaps and velcro closer.

Item		• •		
No.	Size	lbs.	pkg.	
911 18	14 1/2" W x 7 3/4" L	.13	1	
				PREVIOUS





antimagnetic, for correct adjusting in high frequency areas.										
Item	10	‡()		—					•••	
No.	mm	Inch	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.
270 09	0.9	.035	15	.59	0.35	.01	94.5	3.7	.14	1
270 13	1.3	.050	15	.59	0.35	.01	94.5	3.7	.14	1
270 18	1.8	.071	15	.59	0.45	.02	94.5	3.7	.14	1
270 26	2.6	.102	15	.59	0.45	.02	94.5	3.7	.14	1
where the state of										

*Metric dimensions actual - Inch dimensions approximate

	Ceramic antistatic 271/PH 0×15 Made in Germany
•	SHOP
074	

271 Ceramic Phillips Screwdriver, With Wiha-Precision Handle, Out of Anti-static Plastic. Blade special ceramic, anti-static, antmagnetic, for correct adjusting in high frequency areas

animagnetic, for correct adjusting in high frequency areas.								
Item	•	—				.		
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.	
271 00	0	15.0	.59	94.5	3.7	.14	1	
*Metric dimensions actual - Inch dimensions approximate								

Metric dimensions actual Inch dimensions approximate



270 90 Ceramic Slotted/Phillips Screwdriver 3 Pc. Set, With Wiha-Precision Handle, Out of Anti-static Plastic. Blade special ceramic, anti-static, antimagnetic,

for correct adjusting in high frequency areas

for contect adjusting in high nequency areas.								
Item		—			₽ ₽			
No.	mm	mm	Size	mm	lbs.	pkg.		
270 90	0.9	15	0	15	.28	1		
	2.6	15						
NEXT								