Würth Elektronik eiSos GmbH & Co. KG **EMC & Inductive Solutions**

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400 eiSos@we-online.de \cdot www.we-online.de



Product / Process Change Notification (PCN) ☐ Major change ☐ Minor change					
PCN #:	PCN_FeSTAR-TEC_20181102	Change Category:			
Affected Series:	7427111x; 7427111xS; 7427113x; 7427113xS	☐ Equipment / Location☐ General Data☐ Material☐ Process			
PCN Date:	August 02, 2018	☐ Product Design			
Effective Date:	November 02, 2018	☑ Shipping / Packaging☐ Supplier			
Contact:	Product Management	Data Sheet Change:			
Phone:	+49 (0) 7942 - 945 5001	□ Yes	⊠ No		
Fax:	+49 (0) 7942 - 945 5179	Attachment:			
E-Mail:	pcn.eisos@we-online.com	□ Yes	⊠ No		
DESCRIPTION AND PURPOSE OF CHANGE:					
In order to internal standardization and to improve the transportation safety, Würth Elektronik will change the outer carton of the packaging and accordingly optimize the Carton Packaging Quantity.					

All products with date code 2018-10-02 or later, will be affected by this packaging change.

Würth Elektronik eiSos GmbH & Co. KG **EMC & Inductive Solutions**

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400 eiSos@we-online.de · www.we-online.de



DETAIL OF CHANGE:

The outer carton size and packaging quantity will change as detailed in the table below. The carton box material will remain double wall corrugated cardboard but changes to a better quality for improved transportation safety.

		Unit	New Packaging	Old Packaging
Carton Packaging Quantity	(CPQ)	pcs	228	190
Standard Packaging Quantity	(SPQ)	pcs	38	38
Number of trays		pcs	6	5
Moisture Impermeable Bag	(MIB)		yes	Yes
Dimensions of the carton	(LxWxH)	mm	400 x 300 x 165	385 x 305 x 135
Dimensions of the tray	(LxWxH)	mm	370 x 280 x 12	370 x 280 x 12
Weight of a CPQ		g	8700	7300
Weight of a SPQ		g	1370	1370





RELIABILITY / QUALIFICATION SUMMARY:

Drop test according to DIN EN 22248 "Packaging; complete, filled transport packages; vertical impact test by dropping (ISO 2248:1985)" has been done.