

-34,5 REF. -[1,358]

RECOMMENDED CABLE STRIPPING DIM'S

3. MECHANICAL:

 $\emptyset 14.5$

[.57]]


A. DURABILITY: 500 CYCLES_MIN.


B. TEMPERATURE RANGE: -65°C TO +165°C

4. CRIMPED FERRULE HEX CRIMP SIZE .429"

5. CRIMPED CONTACT PIN HEX CRIMP SIZE . 118" FOR ULTRAFLEX CABLE ONLY.

6> SHOWS CABLE ENTRY DIMENSIONS.





[.622] [.138]

- 15,8

CUSTOMER OUTLINE DRAWING

REVISIONS

DATE

0 I - May - 04

06-Nov-06

17-Jun-16

Ø12,4

[.488]

6

Ø10.9

[.429]

ECO

02465

SCALE 1.000

APPR

GRS

GRS

SH

DESCRIPTION

UPDATED DRAWING FORMAT

REVISE CRIMP NOTE 5 TO . 118" HEX CRIMP

SYNC, UPDATED SPRING MATERIAL TO BeCu

\RD-DM16061301M

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

	0.5 - 6mm	6 - 30mm	30 - I20mm	ANGLES
± 0.05mm	\pm 0 . Imm	\pm 0.2mm	\pm 0.3mm	± I°
NOTICE - These	drawings, specific	ations, or other	data (I) are, and	remain the
			upon request; and	
			n other than those	
			ese drawings, spec	
			son to anyone for	
			any manner licens	
			son to manufacture	
			, that may in any	way be related to
or disclosed by	said drawings, sp	pecifications, or	other data.	

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:

-STAMP (IF ANY)

MATERIAL	DRAWN M.ZHANG	DATE 16 - Jun - 16	T
_	ENGINEER K.LI	DATE 18-Jul-05	
REFERENCE AND	APPROVED S.HSIEH	DATE 16 - Jun - 16	SC
CONFIGURATION LEVEL: In Work	CAD FILE		

 \emptyset 9, 3

[.291]

TITLE	
BNC CRIMP PL	UG
(FOR BELDEN	8214,
9913, 9914 C	ABLE)
SCALE: 4.0:1.0 SHEET	2 OF 2
DWG SIZE	REV

ŀ	Amphenol	RF
	www.amphenolrf.c	om
RAWING	NO.BII2IA6-NT	3G - 99

DRAWI	NG	NO.BII2IA6-NT3G-99I3-50
ITEM	NO.	0 2 A A U 9 3 N A 5 F
PART	NO.	112563