	- م -	n m		0	Ξ	Þ]
	4							4
CHARCTERISTICS Schadard : issed on MIL-DTL-38999 Series II Schadard : issed on MIL-DTL-38999 Series II Schell Material ::::::::::::::::::::::::::::::::::::				LAYOUT SHOWN A	AS EXAMPLE			3
Standard : Based on MIL DTL : 38999 Series III Solution introduction in the integration is the integration of the integratint of the integration of the integration of the inte	K	Yeying Shown as example						
Shell Material : Aluminium Shell Material : Aluminium Shell Material : Nickel								
-Durability :: 500 Mating cycles -Delivered without Souriau contacts -Temperature Range :: 65°C to +200°C -Salt Spray :: 48 hours BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 This document is the property of souriau to the reproduced or communicated without permission	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	ØS 35.7 Max Z 31 Max		due to a use of the Products the Specifications issued by eithe (professional recommen	s which does not comply we er of the Parties or by a thi adation, technical notice.) untry Jurisdiction	vith ird party & Control List		2
-Salt Spray : 48 hours -Salt Spray : 48 hours A 14-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 				PN: 8D51	7F22SNL			
Image: Basic series: 8D 5 - 17 F 22 S N L Image: Solution - by contacts in the property of solution - by contacts is the property of solution - by contact without permission			A 14-10-2016	First Release				-
BASIC SERIES: 8D 5 - 17 F 22 S N L SHELL TYPE : Plug with RFI Shielding SCALE Aluminium Plug 8D series 859 859 1 1 CONTACT TYPE : Standard Crimp Contact ORIENTATION : N ORIENTATION : N CONTACT TYPE : SOCKET(500 Matings) SOURIAU WWW.SOURIAU.COM This document is the property of souriau 1					CUS		MOD N°	-
A BASIC SERIES. BD SHELL TYPE BUIL SIZE : 17 F ZZ S N L NA Tolerances: BS59 SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU This document is the property of SOURIAU SOURIAU This document is th			TITLE	TITLE Aluminium Plug 8D series				-
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU SOURIAU SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings)			-					1
	CONTACT TYPE : Standard Crimp Contact		ORIENTATION : N SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or					
	PLATING : F = Nickel		22 FORMAT		U DRG N°		SHEET	
A3 8D517F22SNL-C 1/2 H G F E D C B A	H G					Δ	1/2]

	<u>т</u>	۵	г П	m		0
4		Contact Layout 22				
3	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0				
	-					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda Count
23					A 14-10-20 ISS DATE	FR PN: 8D5171
_					Designed By: TITLE SCALE NA	Date: Alumin General linear Tolerances: ±
	H	G	F	E	FORMAT A3	U WWW.SOURIAU.C SOURIAU 8D517F2

