VIEW ON MATING SIDE

	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
c	C		C		C		C		C		C		C		C		C		C		C		C		C		C		C		C	
b																																
a	A		A		A		A		A		A		A		A		A		A		A		A		A		A		A		A	

A = 16 STANDARD CONTACTS L = 3
C = 16 STANDARD CONTACTS L = 3
S = 32 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

C	G2/0	c2,4,6....32
A	G2/0	a2,4,6....32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO: 2004-XXXX
DRWN: N.S. 09/09/03
CH'K: G.L. 09/09/03
APPR: G.L. 09/09/03
DESCRIPTION
REV
C

QUALITY SYMBOLS
MAJOR =
CRITICAL C =

GENERAL TOLERANCES: (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±0.	±.
3 PLACES	±0.	±.
2 PLACES	±0.	±.
1 PLACE	±0.	±.
ANGULAR: ±		°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SCALE
DESIGN UNITS ☒mm ☐INCH
DRAWN BY & DATE S.S. 10/09/1999
CHECKED BY & DATE G.L. 10/09/1999
APPROVED BY & DATE G.L. 10/09/1999
CAD FILENAME SD-85003-0220.SO1
MATERIAL NO. 85003-0220
DRAWING NO. SD-85003-0220
SHEET NO. 1 OF 1
SIZE D

THIRD ANGLE PROJECTION
DIMENSIONS: ☐mm/INCH ☐INCH/mm ☒mm ONLY
SHT REV
REVISE ON CAD ONLY

TITLE: 96 POS MALE CONNECTOR
ACCORDING DIN 41612 STYLE C CONTACTS
ARRANGEMENT

molex MOLEX INCORPORATED

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.