

# Thermal Pad 21-217

Version TDS.21-217.V.B.1

## Description

Through innovative technology, this soft and conformable thermal pad is designed to provide high level of thermal performance with minimum pressure on electronic components.



## Typical Properties

Properties	Thermal Pad 21-217	Test Method
Thermal	Thermal Conductivity (W/m-K)	1.7
	Continuous Use Temp. (°C)	-55~200
Physical	Color	Black
	Substrate	Silicone
	Density (g/cm <sup>3</sup> )	2.76
	Thickness Range (mm)	0.5~5
	Thickness Tolerance	-
	> 1mm	±10%
	<= 1mm	±0.1mm
Electrical	Hardness (Shore 00)	40
	Outgassing, %TML	0.093
	Outgassing, %CVCM	0.027
	Dielectric Breakdown Voltage (KVAC/mm)	>5
	Dielectric Constant@1MHz	3.3
Regulatory	Volume Resistivity (ohm-cm)	>10 <sup>13</sup>
	Flame Rating	V0
	RoHS	YES
	Shelf Life (months)	24


## Benefits

- Cost-Effective Solution
- Good Compression
- Higher Breakdown Voltage
- Easy For Installation
- RoHS Compliant

## Applications


- Memory Modules
- Mass Storage Devices
- Automotive Electronics
- Telecommunication Hardware
- Radios
- Power Electronics
- Set-Top Boxes
- Audio And Video Players
- IT Infrastructure

## Compression Deflection



21-217Gap Pad 1.0mm thick;  
1 inch<sup>2</sup> test sample;  
Rate of strain = 1.0 mm/min

## Thermal Resistance VS Compression



21-217 Gap Pad 1.0mm thick;  
1 inch<sup>2</sup> test sample;  
Pressure step = 10psi

**Recommended Compression** 20% ~ 30%

**Standard Size** 16" X 8" (406mmX203mm)

**Storage Requirement** Room Temperature Between 20 to 25 degree

**Storage Requirement** R.H. 50%

## Declaimers

- The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the issuing date of this TDS. When using our products, no matter what type of equipment they might be used for, be sure to make a written agreement on the specifications with us in advance. The design and specifications in this TDS are subject to change without prior notice.
- Do not use the products beyond the specifications described in this TDS. This TDS explains the typical performance of the products as individual component. Before use, check and evaluate their operations when installed in your products.
- Install the following systems for a failsafe design to ensure safety if these products are to be used in equipment where a defect in these products may cause the loss of human life or other significant damage, such as damage to vehicles (automobile, train, vessel), traffic lights, medical equipment, aerospace equipment, electric heating appliances, combustion/gas equipment, rotating equipment, and disaster/crime prevention equipment.

JONES TECH PLC  
3 Dong Huan Zhong Road, BDA, Beijing 100176 China  
TEL: +86 10 6786 2636 FAX: +86 10 67860291  
E-mail: sales@jones-corp.com

