



Product: <u>6320UL</u>

Fire Alarm, #18-2c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 2-18 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable Appli	cations:	F	ire Alarm	, Monitor/Dete	ection, Circ	cuits: Au	dio, Contro	I, Initiating, N	otificatio
onstructi	on Deta	ils							
onductor									
Element	Number o	of Element	Size	Stranding	Mate	rial			
Conductor(s)	2		18 AWG	Solid	BC - Bare	e Copper			
nsulation							-		
Element	Ma	aterial	Nom	n. Thickness	Nom. In	sulation	Diameter	Color Code	
Conductor(s)	PVC - Pol	yvinyl Chlori	de 0.008	3 in (0.20 mm) 0.057 in	(1.4 mn	1)	Black, Red	
Outer Jacket									
Mater	ial	Nom. Thic	kness	Nom. Diam	eter Ri	pcord			
PVC - Polyvin	yl Chloride	0.015 in (0.	.38 mm)	0.144 in (3.6	6 mm) Ye	es			
Overall Cable	Diameter (I	Nominal): 0	.144 in (3	5.66 mm)					
	Characte	eristics							
	Characte	eristics							
		eristics	R Nom.	Capacitance	Cond-to-	Cond	Ма	x. Current	
Electricals Element	Nom. Cor	nductor DCF	_	Capacitance ft (100 pF/m)				x. Current r conductor () 25°C
Electricals Element Conductor(s)	Nom. Cor	nductor DCF	_) 25°C
Electricals Element Conductor(s)	Nom. Con 6.4 Ohm/1	nductor DCF	_) 25°C
Electricals Element Conductor(s) /oltage UL Voltage R	Nom. Con 6.4 Ohm/1	nductor DCF	_) 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V	Nom. Cor 6.4 Ohm/1 Rating	ouctor DCF	31 pF/) 25°C
Electricals Element Conductor(s) /oltage UL Voltage R	Nom. Cor 6.4 Ohm/1 Rating	ouctor DCF	31 pF/) 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V	Nom. Cor 6.4 Ohm/1 Rating	ouctor DCF	31 pF/						⊉ 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V Mechanica	Nom. Cor 6.4 Ohm/1 ating	ouctor DCF	31 pF/						0 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V Mechanica Temperature UL Temperat	Nom. Cor 6.4 Ohm/1 tating	oductor DCF	31 pF/						€ 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V Mechanica	Nom. Cor 6.4 Ohm/1 tating	nductor DCF 000ft Cteristics	31 pF/						€ 25°C
Electricals Element Conductor(s) /oltage UL Voltage R 300 V Mechanica Femperature UL Temperat 75°C	Nom. Cor 6.4 Ohm/1 tating Il Charace ure Oper 0°C to	nductor DCF 000ft Cteristics	31 pF/) 25°C
Electricals Element Conductor(s) Voltage UL Voltage R 300 V Vechanica Temperature UL Temperat 75°C	Nom. Cor 6.4 Ohm/1 tating Il Charact 0°C to 1in. Insta	rating	31 pF/						9 25°C
Electricals Element Conductor(s) Voltage UL Voltage R 300 V Vechanica Femperature UL Temperature JL Temperature Stend Radius Stationary M	Nom. Cor 6.4 Ohm/1 ating all Charace 0°C to 1in. Insta mm) 1.15 i	rating 1 +75°C Ilation Min. n (29.2 mm)	31 pF/	ft (100 pF/m)					€ 25°C

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum)
NEC / UL Compliance:	Article 760, FPLP
European Directive Compliance:	EU CE Mark
Other Standard Compliance(s):	California State Fire Marshall
Non-Plenum Number:	5320UL

History

Update and Revision:

Revision Number: 0.417 Revision Date: 01-20-2023

Part Numbers

Variants

Item #	Color	UPC
6320UL 0101000	Black	612825175919
6320UL 010C500	Black	612825175896
6320UL 010U1000	Black	612825175902
6320UL D15C500	Blue	612825175766
6320UL 0051000	Green, Dark	612825175841
6320UL 005U1000	Green, Dark	612825175834
6320UL 0031000	Orange	612825175810
6320UL 003U1000	Orange	612825175803
6320UL 012U1000	Pink	612825175926
6320UL 0021000	Red	612825175797
6320UL 002U1000	Red	612825175773
6320UL 002U500	Red	612825175780
6320UL 007C500	Violet	612825175858
6320UL 007U1000	Violet	612825175865
6320UL 009C500	White	612825175872
6320UL 009U1000	White	612825175889
6320UL 004U1000	Yellow	612825175827

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.