HellermannTyton

Straight Nylon Fittings, w/ Brass Swivel External Metric Thread, IP68, HGL-SM Series

Straight fitting features a snap-on design and a nickel-plated brass metric thread that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. Choose from IP66 or IP68 ingress protection rated fittings.



Conduit Size		Euro Size	HellermannTyton Part Number	Manufacturer Reference Number	Metric Thread	Dimensions									
					А	В		С		D		E		F (A/F)	
in.	mm	(NW)				in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
3/8	16	12	HGL038-SM-M16	FPAX16-BM16	M16 X 1.5	0.47	12	1.77	45	1.14	29	0.43	11.0	0.79	20
1/2	21	17	HGL050-SM-M20	FPAX21-BM20	M20 X 1.5	0.47	12	1.77	45	1.26	32	0.57	14.5	0.94	24
3/4	28	23	HGL075-SM-M25	FPAX28-BM25	M25 X 1.5	0.47	12	1.97	50	1.73	44	0.77	19.5	1.14	29
1.00	34	29	HGL100-SM-M32	FPAX34-BM32	M32 X 1.5	0.51	13	2.13	54	2.01	51	1.04	26.5	1.5	38
1.25	42	36	HGL125-SM-M40	FPAX42-BM40	M40 X 1.5	0.59	15	2.52	64	2.48	63	1.28	32.5	1.97	50
1.50	54	48	HGL150-SM-M50	FPAX54-BM50	M50 X 1.5	0.67	17	2.68	68	2.99	76	1.65	42.0	2.28	58

Technical Properties and Performance									
Property	Rating								
Material:	Body: Nylon PA66 & Nickel Plated Brass								
Application:	Suitable for knockouts and Metric threaded entry								
IP (Ingress Protection)	IP66+IP67+IP68 (2 bar)+IP69K								
Temperature Range	-50°C to +135°C								
Color	Black								
Thread Pattern	Metric								
Supplied with neoprene face seal washer	No								
Suitable for fine or coarse pitch conduits	Yes								
UL Recognized (File E229161)	No								
UL Listed (File No. E247502)	No								
UV Resistant	Yes								
Halogen, Sulphur and Phosphorous free	Yes								
Anti vibration and Tamper Resistant	Yes								
Flammability: UL 94	V2								
Country of Origin	United Kingdom								





Warranty Policy HellermannTyton products are warranted to be free from defects in material and workmanship at the time sold by us; but our obligation under this warranty and that of the seller is limited to the replacement of the product, and neither we nor the seller are bound by any other warranty, expressed, implied or statutory. Under no circumstances are we or the seller liable for any loss, damage, expenses or consequential damages of any kind arising out of the use or inability to use these products. All are sold with the understanding that the user will test them in actual use and determine their adaptability for the intended uses. Every effort is made to ensure accuracy and completeness when describing the technical properties of these products.