

NOTES:

MATERIAL:

HOUSING:

L.C.P SERIES, UL-94V-0 CONTACT: **COPPER ALLOY**

> 10μ" GOLD PLATING ON CONTACT AREA MATTE TIN PLATING ON SOLDER TAIL OVER

NICKEL UNDER PLATING

OPERATION TEMPERATURE: -55°C TO 85°C

ELECTRICAL:

CURRENT RATING: 0.5A 50V AC **VOLTAGE RATING: INSULATION RESISTANCE:** $500M\Omega$ MIN.

CONTACT RESISTANCE: 50ΜΩ ΜΑΧ. DIELECTRIC WITHSTANDING VOLTAGE: 150V AC / 60 SEC.

: CRITICAL DIMENSION

MARKED (C) DIMENSIONS NEED TO BE M TOLERANCE UNLESS OTHERWISE SPECIFIED ±0.15 .XX ±0.10 .XXX ±0.05 THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER **ORIGINAL**

(1)

MEASURED IN CPK	
PIN 150	0
PIN 148	9
4.900 "L" :LONG PIN	





EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED.OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	ACAD REFERENCE NO.: 473-15	50-571-002	
	DRAWN: W.T	DATE: JUNE.28 /2018	
	CHECKED:	DATE:	
	SCALE: N.T.S	SHEET 2 OF 2	
	DRAWING NUMBER: 473-150-571-002		

473-150-571-002

PART NUMBER:

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.