



## NOTE: MATERIAL HOUSING: PBT UL94V-0, BLACK CONTACT: **BRASS** NUT: **BRASS** D-RING: EPDM, BLACK FINISH CONTACT: GOLD PLATED DVER 50u" NICKEL NUT: NICKEL PLATED SHELL: NICKEL PLATED **ELECTRICAL** RATED CURRENT: 1.5A RATED VOLTAGE: 30V INSULATION RESISTANCE: 100 MOhms MIN. CONTACT RESISTANCE: 10 mOhms MAX. WATER PROOF: IP67 **ENVIRONMENT**

-40°C TD +85°C

22





**OPERATION TEMPERATURE:** 

MAX WIRE AWG:

## COMPLIANT

UNITS = INCHES [MM]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

| M. SIGMON | DATE:<br>03-08-16 |
|-----------|-------------------|
|           |                   |

NorComp

|        |       | ואומושו |   |     |
|--------|-------|---------|---|-----|
| SCALE: | SHEET | OF      |   | REV |
| NTS    |       | 1       | 1 | 5   |

DWG NO. 858-012-203RSUY