

Product Change Notification / SYST-13HAHH517

Date:

16-Jan-2023

Product Category:

Ethernet Bridges

PCN Type:

Document Change

Notification Subject:

Data Sheet - LAN7430/LAN7431 Low Power PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC / PHY - Data Sheet

Affected CPNs:

SYST-13HAHH517_Affected_CPN_01162023.pdf SYST-13HAHH517_Affected_CPN_01162023.csv

Notification Text:

SYST-13HAHH517

Microchip has released a new Datasheet for the LAN7430/LAN7431 Low Power PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC / PHY - Data Sheet of devices. If you are using one of these devices please read the document located at LAN7430/LAN7431 Low Power PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC / PHY - Data Sheet.

Notification Status: Final

Description of Change:

1. Product Features - Removed the following features: LinkMD[®] TDR-Based cable diagnostic, Signal Quality Indicator, Quiet-WIRE[®] technology, and Signal Quality Indicator (SQI) support.

- 2. Section 1.4, "Reference Documents" Updated reference documents to latest URLs.
- 3. Table 2-1, "LAN7430/LAN7431 Family Feature Matrix" Updated to remove automotive option from LAN7430.
- 4. Section 2.1, "General Description", Section 6.6, "IEEE 1588v2 (PTP)" Updated "delay mechanisms" to "delay request mechanisms."

5. Product Features, Section 6.6, "IEEE 1588v2 (PTP)" - Updated 1588 (PTP) master/slave language to "timeTransmitter/timeReceiver".

6. Section 6.6.1, "IEEE 1588-2008" Updated "Grand Master Clock" to "Grandmaster Clock".

7. Section 6.12.9, Ethernet PHY Software Reset Text updated from "An optional 125ms delay can be enabled to allow for the external PHY to become ready. This is enabled with the External PHY Ready Delay Enable (EXT_PHY_RDY_EN) bit." to "A 125 ms delay is enabled for the external PHY to become ready after software reset. This can be disabled by clearing the External PHY Ready Delay Enable (EXT_PHY_RDY_EN) bit."

8. Section 7.1, "Absolute Maximum Ratings*" HBM updated from "±2kV" to "±3kV".

9. Section 8.0, "Package Information" Top markings for both LAN7430 and LAN7431 have been added to the document.
10. Section, "Highlights", Section TABLE 2-1, "LAN7430/LAN7431 Family Feature Matrix", Section 7.3, "Package Thermal Specifications", Section 8.0, "Package Information", Product Identification System Updated to reflect package type changed from "SQFN" to "VQFN".
11. Throughout Document Added "Automotive for LAN7431 only" where appropriate.

Impacts to Data Sheet: None

Reason for Change: To Improve Productivity

Change Implementation Status: Complete

Date Document Changes Effective: 16 Jan 2023

NOTE: Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

Attachments:

LAN7430/LAN7431 Low Power PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC / PHY - Data Sheet

Please contact your local Microchip sales office with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to <u>receive Microchip PCNs via email</u> please register for our PCN email service at our PCN home page select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the PCN FAQ section.

If you wish to <u>change your PCN profile</u>, <u>including opt out</u>, please go to the <u>PCN home page</u> select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections. Affected Catalog Part Numbers (CPN)

LAN7430/Y9X LAN7431/YXX LAN7430-I/Y9X LAN7431-I/YXX LAN7431-V/YXX LAN7431-V/YXXVAO LAN7431T-V/YXXV01 LAN7431T-V/YXXV02 LAN7431T-V/YXXVAO LAN7430T/Y9X LAN7430T/Y9X LAN7430T-I/Y9X