
3|

4


 PRODUCT NUMBER
 PITCH

 KXxxC1x000J0G
 15.00 mm



DIM L

DIM P



M

Material:

●Item@Terminal housing:Thermoplastic (UL94V-0)

●Item (UL94V-0) Terminal cover: Thermoplastic

●Item ⓒ Female contact : Copper. Tin plated

●Item (d) Wire guard: Stainless Steel

●Item@Clamp: Steel Stamping, Zinc plated

●Item (f)Terminal screw: Steel, Zinc plating"-"slot type,M5

Electrical: cULus
• Voltage rating: 600 V
• Current rating: 115 A

• Wire range:

Solid wire(AWG): 2-20
 Stranded wire(AWG): 2-20
 Torque(Lb-In): 36.5
 Screw: M5
 Wire strip length: 19-20mm

• Withstanding Voltage: 2.2 KV

●Operating temperature: -40°C to +115°C

• Safety Approval: callus

N=Number of poles DIM L=(N-1)x15.0+16.3 DIM P=(N-1)x15.0

8.15

15.00

• •		
	poles	Tolerance
	2-4p	±0.20
	5-7p	±0.35
	8-10p	±0.50

1

PART NO.: KX xx C 1 x 0 00J0 G

Color RoHS compliant
Solid block 0 Black (RAL9005) (lead<4%)
No. of poles 2 Red (RAL3001/D) In copper Alloy
02 2 poles 3 Orange (RAL2011/P)

03 3 poles 4 Yellow(RAL1018/A)
... ... 5 Green(RAL6018/T)
10 10 poles 6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

mat'l. code surface tolerance projection product family TERMINAL BLOCK ASME Y14.5 V ASME Y14.5 Itr ecn no dr date tolerances unless otherwise specified title ММ X.±0.5 angles 🛭 TERMINAL BLOCK X.X±0.3 PLUGGABLE PLUG X*±1* X.XX±0.1 scale EVIN ZHONG 050914 dwg no sheet 1 of 1 size 050914 engr EVIN ZHONG KXxxC1x000J0G 050914 chr HANKE FENG appd SHI JUN 050914 type CUSTOMER Drawing sheet revision index sheet

В

form: A4mmXLc

2

PDS: Rev :A 3

STATUS:Released

Printed: Jul 01, 4014