

p.800.522.5546 f.800.521.0844 12780 Danielson Ct., Ste. A Poway, CA 92064

PRODUCT CHANGE NOTIFICATION

PCN Number: 379

Date of Issue:	05/16/2016	
PCN Effective Date:	05/16/2016	
Last Time Buy Date:	N/A	
Last Time Ship Date:	N/A	
Type of Change:	DESIGN	
Title of Change:	DESIGN 4302H3-5V 5101H3-5V 5102H3-5V 5302H3-5V 5380H3-5V	
Reason of Change:	Please be informed that VCC updated the datasheet of the 4302H, 5101H, 5102H, 5302H, 5380H Series for Part Numbers below. Technical information were updated. See the changes on the next page. New datasheets are available on the website.	

Sannah Vinding Sannah Vinding Sannah Vinding

VCC Contact Name: customerservice@vcclite.com Phone Number: (800) 522-5546 Form 7.2.3-1 Product Change Notification Rev 02/11/2016



p.800.522.5546 **f**.800.521.0844 12780 Danielson Ct., Ste. A Poway, CA 92064

AFFECTED PART NUMBER			
Part Number	Description	Change(s)	
4302H3-5V	LED TH 5mm 5V 10mA 8mcd Amber	luminosity min (from 2 to 2.2 mcd) luminosity typ (from 8 to - mcd) Dimensions updated	
5101H3-5V	PMI RND .25" LED 5V Wire AMB	luminosity (from 8 to 10 mcd) wavelength (from 583 to 585 nm) rated current (from 10 to 20 mA)	
5102H3-5V	PMI RND .25" LED 5V Wire AMB	luminosity (from 8 to 10 mcd) wavelength (from 583 to 585 nm) rated current (from 10 to 20 mA)	
5302H3-5V	CBI 5mm 1POS Right Angle 5.0V Amber	luminosity (from 8 to 10 mcd) wavelength (from 583 to 585 nm) rated current (from 10 to 20 mA)	
5380H3-5V	CBI 5mm 1POS R. Angle 5V Amber	luminosity (from 8 to 10 mcd) wavelength (from 583 to 585 nm) rated current (from 10 to 20 mA)	