Miniature Incandescent Indicators

FOR MOUNTING IN 11/16 CLEARANCE HOLE 6V TO 120V OPERATION



T - 2 WITH TELEPHONE SLIDE BASE (PSB type)

See lamp ratings on page J.




MATERIALS AND FINISHES

- Mounting Bushing and Lens Holder: Brass, white nickel finish. Optional—polished chrome.
- Mounting Nut: Steel, cadmium plated with yellow iridescent chromate finish.
- Internal-tooth Lockwasher: Steel, cadmium plated with yellow iridescent chromate finish.
- Terminals: Amp Connector No. 42198-2. Brass, white nickel finish. Leads may be soldered through holes provided in the contacts.
- Lens Cap: (52-, 95-, 135- Series)-High temperature plastic.

95 SERIES 52 SERIES 135 SERIES

NOTE: To specify optional polished chrome finish, change the first digit of the catalog number suffix from "1" to "3". Example: 135–1059–3273–302.

WITH SCREW-IN LENS CAPS



81 SERIES
BASE PART NUMBER

95-1059-3171-102

52-1059-3191-102

Stovepipe lens

Stovepipe lens



135-1059-3271-102

Cylindrical lens



81-1059-0111-102

Convex lens



81-1059-0431-102

Faceted lens

CAP PART NUMBERS COMPLETE ASSEMBLY PART NUMBERS STOVEPIPE 95-3171 translucent 95-1059-3171-102 52-3191 internal fluting 52-1059-3191-102 9/16 - 27 NS THD. CYLINDRICAL 135-3271 translucent 135-1059-3271-102 81-0111-100 back frosted 81-1059-0111-102 **FACETED** 81-0431-100 unfrosted 81-1059-0431-102

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.

