



2) MATERIALS:

-HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-O.

-SIGNAL CONTACT - COPPER ALLOY.

-POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.

(3) PLATING SPECIFICATION: 10116351

- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) I.15±0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02±0.07MM HOLE.
- 8) PRODUCT SPECIFICATION: GS-12-658.

 APPLICATION SPECIFICATION: GS-20-141.

 PRODUCT PACKAGE SPECIFICATION: GS-14-1502.
 - 9) A SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

元》

projection scale size MM3:2 e n q Zhen-Hua Liu \oplus Chr Fancy Zhang 2015/10/16 ecn no PwrBlade+ rel level Released 2015/10/16 product family 4ACP + 48S + 12HDP10106263-G012002 RA PF HEADER www.fci.com cat. no. Product - Customer Drw sheet 3 of 3

Pro/E File - REV C - 2009-06-09

2

PDS: Rev :C

3

STATUS:Released

Printed: Oct 19, 2015

D