P	i.	-	1	-	1	į	ļ		1	1	-	
þ		1	1	-	-				1	-	-	
þ		-	-	-	-	-		1		1	1000	

..........

General ordering data

Order No. Part designation Version

EAN Qty.

Markings

Cadmium
Can be labelled with thermal transfer printers
Can be printed with plotter
Can be written with dot-matrix printer
Can be written with laser printer
Colour of printing
Function
Halogen
Length
Material
Material colour
Material colour according to resistance code
Max. temperature, continuous
Min. temperature, continuous
Orientation of print
Pin can be written (STI)
Pitch
PrintJet
Printed characters
Printing method
Silicone
Speed marking laser
Type of printing
UL 94 flammability class
Vibration-proof
Width

1646640000 ZS 15/5 MC BEDRUCKT Connector markers, L x W: 15 x 5 mm, Polyamide + POM, white 4008190456696 96 pc(s).

	no
S	No
	Yes
	No
	No
	black
	Connector markers
	no
	15 mm
	Polyamide + POM
	white
;	9
	100 °C
	-40 °C
	horizontal and vertical
	No
	5 mm
	No
	Mixed characters
	MC Laser
	no
	Yes
	To customer specification
	V2
	as for IEC 68-2-6
	5 mm



Markings		
Approvals		
Approvals institutes	n.a.	
Classifications		
eClass 4.1	24-19-02-19	
eClass 5.0	27-14-11-37	
eClass 5.1	27-14-11-37	
Similar products		

Order No.		Version
1610010000	ZS 10/5 MC ***SPECIFY TEXT***	Connector markers, L x W: 10 x 5 mm, Polyamide + POM, white
1610030000	ZS 12/6 ***SPECIFY TEXT***	Connector markers, L x W: 12 x 6 mm, Polyamide + POM, white

