## IEC Appliance Outlet F, Screw-on Mounting, Rear Side, PCB-/Solder Terminal





# Description

- Panel mount :
- Screw-on mounting from rear-side
- 1 Function
- Connector , Pin temperature 70 °C , protection class I or II
- For PCB mounting

See below: Approvals and Compliances

Other versions on request - For protection class II

#### References

Substitute for type P675/PC Alternative: protection class II version

#### Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Accessories, Detailed request for product

#### **Technical Data**

10A / 250VAC; 50Hz	appliance inlet/-outlet	F acc. to IEC 60320-3
15 A / 250 VAC; 60 Hz		UL 60320-1, CSA C22.2 no. 60320-1
> 4 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)		(for cold conditions) pin-temperature 70 °C, 10A, Protection Class I or II
-25 °C to 70 °C		
from front side IP20 acc. to IEC 60529		
Suitable for appliances with protection class I or II acc. to IEC 61140		
For PCB mounting : Ground terminal: Solder terminal straight		
PA6, black, UL 94V-0		
	15A / 250VAC; 60Hz   > 4 kVAC between L-N   > 2 kVAC between L/N-PE   (1 min/50 Hz)   -25 °C to 70 °C   from front side IP20 acc. to IEC 60529   Suitable for appliances with protection class I or II acc. to IEC 61140   For PCB mounting : Ground terminal: Solder terminal straight	15A / 250VAC; 60Hz   > 4 kVAC between L-N   > 2 kVAC between L/N-PE   (1 min/50 Hz)   -25 °C to 70 °C   from front side IP20 acc. to IEC 60529   Suitable for appliances with protection   class I or II acc. to IEC 61140   For PCB mounting : Ground terminal:   Solder terminal straight

### **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 5001

Approval Logo	Certificates	Certification Body	Description
<b>1</b> 05	KEMA Approvals	KEMA	Certificate Number: 71-104273, 71-104274 (PC I & PC II @ KEMA)
c <b>FL</b> <sup>°</sup> us	UL Approvals	UL	UL File Number: E103791
	CCC Approvals	ССС	CCC Certificate Number: 2015180204000595 (PC I only / nur SK I)

## Product standards

Product standards that are referenced

Organization	Design	Standard	Description
IEC.	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
IEC	Designed according to	IEC 60320-3	Appliance couplers for household and similar general purposes
(l)	Designed according to	UL 60320-1	Standard for Attachment Plugs and Receptacles
	Designed according to	CSA C22.2 no. 60320-1	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

## **Application standards**

Application standards where the product can be used

Organization	Design	Standard	Description
IEC.	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technology equipment.

## Compliances

The product complies with following Guide Lines

	0		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/836
<b>©</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

## Dimensions [mm]



# Config. Code

# 5001 - H - A B C 0- D - E

The characters are placeholders for the correspondingly keys of selections from the key tables.

# 5001 - **H** - A B C 0- D - E **= Type**

Туре	Configuration key
protection class II	В
protection class I	X

# 5001 - H - A B C 0- D - E = Terminals

Terminal Ground	Configuration key
without terminal	0
PCB-terminal long (additional solder terminal)	6
Symbols similar as in table A	

## 5001 - H - A B C 0- D - E = Terminals

Terminal L	Configuration key
PCB-terminal standard	4

# 5001 - H - A B C 0- **D** - E **= Color**

5001 - H - A B C 0- D - **E** = Style

Color	Configuration key
Black	A

# 5001 - H - A B C 0- D - E = Terminals

Terminal N	Configuration key	Style	Configuration key
PCB-terminal standard	4	flange with through holes	2
Symbols similar as in table A		hange with allough holes	L

## All Variants

Туре Те	rminals L / N	Terminal Ground	Color	Style	Features	Config. Code	Order Number
		PCB-terminal long (additional solder terminal)	black	Flange with through holes	-	5001-X-4460-A-2	6182.0033

### Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

## Mating Inlets/Plugs

### Category / Description

#### Plug Overview complete



4732, Mounting: Power Cord, Plug: IEC E, Cable	4732
4735, Mounting: Power Cord, Plug: IEC E, Cable	4735
9009, Mounting: Plug: IEC E, Screw clamps	9009
4733, Mounting: Power Cord, Plug: IEC E, Cable	4733
4736, Mounting: Power Cord, Plug: IEC E, Cable	4736
Plug further types to 5001	

05.07.2019