VIEW ON TERMINATION SIDE

	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
B	Y	Y	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	Y	Y
A	Z	Z	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	Z	Z

A = 28 STANDARD CONTACTS L=3
B = 28 STANDARD CONTACTS L=3
Z = 4 FMLB CONTACTS +0,6 L=3
Y = 4 FMLB CONTACTS +0,6 L=3

S = 64 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85001-0001 sht.1
Technical Data	PS-85003-0001

Contact symbol	Perform. level	Contact position number
Y	G2/0	b1,2,31,32,
Z	G2/0	a1,2,31,32
B	G2/0	b3-30
A	G2/0	a3-30

see ECN No. 2204
96/07/18 Ca

REVISIONS

LTR

C

FOR PREVIOUS REVISIONS SEE MRI LIST

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2°

	INCH	METRIC
3 PLACE	± .	±
2 PLACE	± .	±
1 PLACE	± .	±

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DESIGN DIMENSION ☐ MM ☐ IN.

EQUIVALENT DIMENSION ☐ MM ☐ IN.

IF TWO DIMENSIONS ARE SHOWN THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY

DRWG BY Ca — SIGN

CHK'D BY KN — SIGN

APP'D BY — SIGN

SCALE

REVISE ONLY ON CAD SYSTEM | SH. | REV.

CADCAM PROJECT NAME s8500103 s81

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TITLE

64 pos. Male connector acc. DIN 41612 style B contacts arrangement

molex MOLEX EUROPE

SHEET NO. 1 OF 1

DATE 95/05/24

PART NO. 85001-0385

DWG NO. SDA-85001-0385

SIZE A