# **Technical** Data Sheet

Rev. A (10/17) Page 1 of 2

## E-Line Contact Cleaner Product# 1622

#### **Product Description**

Hydrocarbon based defluxer formulated to be powerful, yet very economical. Eliminates brushing and scrubbing, saving time and materials. Clean oxidation, oil, and other contaminants from contacts, metal switches, relays, edge connectors, buss bars, and circuit breakers.

TECHSPRAY

#### **Features / Benefits**

- Powerful cleaner
- Ideal for sensitive plastics
- Low toxicity
- Non-ozone depleting
- Zero residue

#### **Usage Instructions**

Disconnect equipment from power source. Hold can 6-8 inches away. When used as a general cleaner, start at top of area to be cleaned using a sweeping motion and spray the area, slowly working toward the bottom. To clean in hard to reach areas, insert extension tube in sprayhead. Allow components to dry completely before applying current.

#### **Plastics & Rubber Compatibility**

MATERIAL NAME	RATING	
ABS:	Excellent	
Nylon:	Excellent	
Lexan:	Excellent	
HDPE:	Excellent	
LDPE:	Excellent	
C.E. Phenolic:	Excellent	
PMMA:	Excellent	
POM:	Excellent	
PP:	Excellent	
PS:	Excellent	
PTFE:	Excellent	
PVC:	Excellent	



#### **Typical Product Data and Physical Properties**

Physical state:	Liquid
Color:	Clear, colorless
Odor:	Characteristic
Vapor pressure:	7.4 kPa <b>(</b> 55.5 mmHg)
Volatility:	100% (w/w)
Evaporation rate:	>1 ((TCE=1) =1)
Aerosol product	
Type of aerosol:	Spray
Heat of combustion:	30.26 kJ/g
Shelf life:	5 years

### E-Line Contact Cleaner Product# 1622

#### **Packaging and Availability**

1622-10S	10 oz. Aerosol (284g)
1622-13S	13 oz. Aerosol (369g)

#### **Environmental Policy**

Techspray<sup>®</sup> is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

#### Resources

Techspray<sup>®</sup> products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray<sup>®</sup> products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.echspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Rev. A (10/17) Page 2 of 2



North America Techspray® 8125 Cobb Center Drive Kennesaw, GA 30152 800-858-4043 tsales@techspray.com

#### Europe

ITW Contamination Control BV Saffierlaan 5, 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 info@itw-cc.com Countries outside the US Call to locate a distributor in your country