<u>96HD3TB-ST-WD5KA</u>



Features

- Built for 24/7 surveillance
- AllFrame technology for better performance
- Designed to support up to 32 HD cameras

Spec

Product94HD3TB-ST-WD5KAProduct DescriptionWD 3.5° 3TB SATAIII 5KRPM 64MB 4K AVApplicationVideo StorageManufacturer Part NumberWD 3DPURXManufacturerWD STERN DIGITALCapacity3TModel GenerationWD PURPLEStarSATAIIIHerfaceSATAIIIPayroperationKeSSpindle Speed60/SArange Read Seek TimeSAINArange Read Seek TimeSa.ImnCapacity TemperatureNo.IND TempMTBFJo0,000 HOURSRehS StatusYES		
ApplicationVideo StorageManufacturer Part NumberWD30PURXManufactur erWESTERN DIGITALCapacity3TModel GenerationWD PURPLESize3.5 INInterfaceSATAIII24X7 OperationYESSpindle Speed6GB/SSpindle Speed64MBAverage Read Seek Time26.1mmOperating TemperatureNonND TempMTBF1,000,000 HQURS	Product	96HD3TB-ST-WD5KA
Manufacturer Part NumberW D30PURXManufactur erW ESTERN DIGITALCapacity3TModel GenerationW D PURPLESize3.5 INInterfaceSATAIII24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time26.1mmOperating TemperatureNonIND TempMTBF1,000,000 HOURS	Product Description	W D 3.5" 3TB SATAIII 5KRPM 64MB 4K AV
Anufactur erWESTERN DIGITALCapacity3TModel GenerationWD PURPLESize3.5 INInterfaceSATAIII24X7 OperationYESMax Transfer RateGB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time26.1mmOperating TemperatureNoIND TempMTBF1,000,00 HOURS	Application	Video Storage
Capacity3TModel GenerationWD PURPLESize3.5 INInterfaceSATAIII24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time2MSThickness26.1mmOperating TemperatureNonIND TempMTBF1,000,000 HOURS	Manufacturer Part Number	W D30PURX
Model GenerationWD PURPLESize3.5 INInterfaceSATAIII24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time26.1mmThickness26.1mmOperating Temperature1,000,000 HOURS	Manufactur er	W ESTERN DIGITAL
Size3.5 NInterfaceSATAIII24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time2MSThickness26.1mmOperating TemperatureNonIND TempMTBF1.000,000 HOURS	Capacity	ЗТ
InterfaceSATAIII24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time2MSThickness26.1mmOperating TemperatureNonIND TempMTBF1,000,000 HOURS	Model Generation	W D PURPLE
24X7 OperationYESMax Transfer Rate6GB/SSpindle Speed5400RPMCache Size64MBAverage Read Seek Time2MSThickness26.1mmOperating TemperatureNonIND TempMTBF1,000,000 HOURS	Size	3.5 IN
Max Transfer Rate 6GB/S Spindle Speed 5400RPM Cache Size 64MB Average Read Seek Time 2MS Thickness 26.1mm Operating Temperature NonIND Temp MTBF 1,000,000 HOURS	Interface	SATAIII
Spindle Speed 5400RPM Cache Size 64MB Average Read Seek Time 2MS Thickness 26.1mm Operating Temperature NonIND Temp MTBF 1,000,000 HOURS	24X7 Operation	YES
Cache Size64MBAverage Read Seek Time2MSThickness26.1mmOperating TemperatureNonIND TempMTBF1,000,000 HOURS	Max Transfer Rate	6GB/S
Average Read Seek Time 2MS Thickness 26.1mm Operating Temperature NonIND Temp MTBF 1,000,000 HOURS	Spindle Speed	5400RPM
Thickness 26.1mm Operating Temperature NonIND Temp MTBF 1,000,000 HOURS	Cache Size	64MB
Operating Temperature NonIND Temp MTBF 1,000,000 HOURS	Average Read Seek Time	2MS
MTBF 1,000,000 HOURS	Thickness	26.1mm
	Operating Temperature	NonIND Temp
RoHS Status YES	MTBF	1,000,000 HOURS
	RoHS Status	YES

ADVANTECH

Peripheral Allied Procurement Services

our Ultimate Sourcing Pa