


High I²t Chip fuse withstands high inrush currents in a 1206 (3216 metric) package



The compact CC12H offers a significant space savings over other larger SMD devices with similar performance.

Product description:

Eaton's Bussmann® series CC12H SMD fuses provides excellent inrush withstand performance coupled with the cycling advantages of a ceramic solid matrix construction.

The CC12H is a cost-effective solution for applications in which high inrush currents and/or on-off cycling are present.

The CC12H allows maximum protection without oversizing of the fuse rating.

Features and benefits:

- High inrush withstand capability.
- AEC-Q200 Grade 1 qualified (750 mA to 20 A versions)
- cURus recognized
- Compact 1206 (3216 metric) design utilizes less board space.
- RoHS compliant, lead free and halogen free construction
- Operating temperature of -55 °C to +125 °C (with derating) (250 mA to 15 A versions) ensuring protection in harsh climates.
- The high I²t values of allows the end user to avoid nuisance openings from high inrush currents and provides additional protection against uncertain current surges from the system.

EATON

Powering Business Worldwide

Specifications

Ratings:

- Voltage rating DC: 32 V to 63 V
- Current rating: 0.25 A to 30 A
- Interrupting rating: 50 A to 200 A

Agency information:

- cURus recognition: File E19180, Guide JDYX2/JDYX8
- AEC-Q200 qualified: (750 mA to 20 A versions)
- RoHS compliant
- REACH declaration available upon request

Packaging and ordering information:


- -TR (3000 parts on a 7" reel, tape width 8 mm)

Ordering Code	
Part Number	-TR option
CC12H250mA	CC12H250mA-TR
CC12H375mA	CC12H375mA-TR
CC12H500mA	CC12H500mA-TR
CC12H750mA	CC12H750mA-TR
CC12H1A	CC12H1A-TR
CC12H1.5A	CC12H1-5A-TR
CC12H2A	CC12H2A-TR
CC12H2.5A	CC12H2-5A-TR
CC12H3A	CC12H3A-TR
CC12H3.5A	CC12H3-5A-TR
CC12H4A	CC12H4A-TR
CC12H4.5A	CC12H4-5A-TR
CC12H5A	CC12H5A-TR
CC12H6A	CC12H6A-TR
CC12H7A	CC12H7A-TR
CC12H8A	CC12H8A-TR
CC12H10A	CC12H10A-TR
CC12H12A	CC12H12A-TR
CC12H15A	CC12H15A-TR
CC12H20A	CC12H20A-TR
CC12H25A	CC12H25A-TR
CC12H30A	CC12H30A-TR

Electrical characteristics:

Amp Rating	% of Amp Rating	Opening Time
250 mA – 30 A	100%	4 hours minimum
1 A – 3 A	200%	1 s – 60 s
25 A – 30 A	200%	120 s max
1 A – 5 A	250%	5 s max
1 A – 5 A	300%	0.1 s – 3 s
250 mA – 750 mA	350%	5 s max
6 A – 20 A	350%	5 s max
250 mA – 500 mA	1000%	0.01 ms – 1 ms
750 mA – 30 A	1000%	0.2 ms – 20 ms

Construction and dimensions mm (in):



Eaton
Electronics Division
 1000 Eaton Boulevard
 Cleveland, OH 44122
 United States
www.eaton.com/elx

© 2016 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. 4025 BU-MC16042
 July 2016

EATON
 Powering Business Worldwide

Eaton is a registered trademark.
 All other trademarks are property of their respective owners.