NSYS3D5420T

Spacial S3D tspt door w/o mount.plate. H500xW400xD200 IP66 IK08 RAL7035.





Main

Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	19.69 in (500 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	7.87 in (200 mm)
Door type	Glass
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock 1 cable gland plate

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	Body steel Door steel and security glass	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	UL DNV GL CUL BV LR	
Net Weight	20.59 lb(US) (9.34 kg)	

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK08 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159435
Nbr. of units in pkg.	1
Package weight(Lbs)	20.59 lb(US) (9.34 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	20.20 in (51.3 cm)	
Package 1 width	16.46 in (41.8 cm)	
Package 1 Length	9.76 in (24.8 cm)	

Offer Sustainability

Green Premium product REACh Declaration Yes
Yes
5
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

Contractual warranty

· · · · · · · · · · · · · · · · · · ·	
Warranty	18 months