

Protect It! 1-Outlet Portable Surge Protector, Direct Plug-In, 750 Joules, Tel/Modem Protection

MODEL NUMBER: TRAVELCUBE











Highlights

- 1 AC outlet
- Direct plug-in design
- Built-in tel/modem surge protection
- 750 joule rating
- Diagnostic LED displays protection status

Package Includes

• TRAVELCUBE surge suppressor

Description

The TRAVELCUBE is designed for convenient portable and economical surge protection. Small and powerful, the TRAVELCUBE features 750 joules and carries \$10K of insurance as well as a lifetime product warranty. Throw it in a briefcase or purse and have quality surge protection wherever you need it — hotel room, dorm, client office — anywhere!

Features

- Portable wall-mount cube stores easily in any bag or briefcase
- 1 NEMA5-15R AC outlet
- 750 joules of protection shields equipment from harmful surges, spikes and line noise
- Diagnostic LED displays protection status
- Built-in tel/modem surge protection
- UL 1449 rated 3rd Edition
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332118486	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	





1 10 11 11 5 1 11	
Input Cord Length Details	Direct plug-in
Voltage Compatibility (VAC)	120
Maximum Surge Amps	36000
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	0
Right-Angle Plug	No
Input Cord Length (m)	0.00
Integrated Cord Clip	No
ОИТРИТ	
Frequency Compatibility	50 / 60 Hz
Output (Watts)	1800
Output Receptacles	(1) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(1) Yes
Right-Angle Outlets	Yes
USER INTERFACE, ALERTS & COI	NTROLS
Diagnostic LED(s)	Yes
Diagnostic LED Details	
Diagnostic LLD Details	Built-in LED confirms suppressor "protection present" (red) status
SURGE / NOISE SUPPRESSION	Built-in LED confirms suppressor "protection present" (red) status
	Built-in LED confirms suppressor "protection present" (red) status 750
SURGE / NOISE SUPPRESSION	
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating	750
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time	750 < 1 ns
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off DATALINE SURGE SUPPRESSION	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details	750 < 1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details Cable (Coax) Protection	750 <1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No 1 line No
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details Cable (Coax) Protection Network (Ethernet) Protection	750 <1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression 500V Up to 20 dB No 1 line No No





Form Factors Supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle
Housing Color	Light Gray
Mounting Holes or Slots	No
Receptacle Color	Gray
Shipping Dimensions (hwd / in.)	1.50 x 4.25 x 6.50
Shipping Dimensions (hwd / cm)	3.81 x 10.80 x 16.51
Shipping Weight (lbs.)	0.20
Shipping Weight (kg)	0.09
Unit Dimensions (hwd / in.)	1.49 x 2.16 x 3.07
Unit Dimensions (hwd / cm)	3.78 x 5.49 x 7.80
Unit Weight (lbs.)	.17
Unit Weight (kg)	0.08
FEATURES & CRECIFICATIONS	
FEATURES & SPECIFICATIONS	
Antimicrobial	No
Rotatable Outlets	No
STANDARDS & COMPLIANCE	
Product Certifications	cUL Listed; UL 1449; UL 497A; UL 1363; UL Listed
Product Compliance	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies