9001KT1 30MM PILOT LIGHT PUSH TO TEST 110-120V





Main

Range of Product	Harmony 9001K
Product or Component Type	Pilot light
Device short name	К

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz	
Shape of screw head	Round	
Operating Mode	Push-to-test	

Environment

Product Certifications	CE	
	CSA LR25490 class 3211 03	
	UL listed file E42259 CCN NKCR	
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	3389118039339	
Nbr. of units in pkg.	1	
Package weight(Lbs)	9.44 oz (267.62 g)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	2.00 in (5.08 cm)	
Package 1 width	2.30 in (5.842 cm)	
Package 1 Length	4.50 in (11.43 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	600	
Package 2 Weight	359.00 lb(US) (162.84 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

18 months