3M 6878/07141 Spectacle Kit

User Instructions (Important: Keep these User Instructions for reference) The 3MTM 6878/07141 Spectacle Kit consists of a frame assembly and a rail assembly. The frame assembly is the holder for the corrective lenses. The rail assembly supports the frame assembly in the facepiece and allows for up and down, in and out positioning of the frame assembly.

- 1. Install rail assembly into facepiece as shown with plastic foot positioned on the center port adapter. (The slot in foot is positioned over ridge on adapter as shown.)
- 2. Install frame assembly onto rail assembly by inserting pins into holes in rubber slide as shown. The top of rail is centered between nubs at top of faceseal. (The rubber slide can be removed from the rail assembly and reversed for additional in and out movement of the frame assembly.)
- 3. Spectacles can now be moved up, down, in or out to obtain optimal fit and vision.
- a) Frame Assembly
- b) Rail Assembly
- c) Rail Foot
- d) Rubber Slide



FOR MORE INFORMATION

In United States, contact:

Internet: www.3M.com/occsafety Technical Assistance: 1-800-243-4630 **For other 3M products:** 1-800-3M-HELPS or 1-651-737-6501

3M Occupational Health and Environmental Safety Division

3M Center, Building 0235-02-W-70 St. Paul, MN 55144-1000

©3M 2003

38-9018-9565-6