

1. OVERALL INSULATION CRIMP DIAMETER, INCLUDING CRIMP BARREL, MUST NOT EXCEED .125 [3.18]

2 LABEL LOCATED APPROXIMATELY WHERE SHOWN.
LABEL INFORMATION AS FOLLOWS:

2387127-X
REV B
TE/MEXICO
MM/DD/YY

TE P/N
CUST REV
MANUFACTURER NAME/COUNTRY OF ORIGIN
DATE CODE

3"L" REPRESENTS THE LENGTH OF THE WIRE USED FOR THE LEADS.

TE PN	LENGTH "L"
2387127-1	0.5M
2387127-2	1.0M
2387127-3	2.0M

4. TOLERANCES PER IPC STANDARD: IPC-A-620A

Metric		
<0.3 m	+25mm -0mm	
>0.3 m - 1.5m	+50mm -0mm	
>1.5 m - 3m	+100mm -0mm	
>3 m - 7.5m	+150mm -0mm	
>7.5m	+5% -0%	

5. HARNESS SHALL BE SHIPPED IN SEALED PLASTIC BAG.

В

- 6. CONTINUITY ELECTRICAL TEST MUST BE PERFORMED.
- 7. WIRE 18 AWG

THIS DRAWING IS A CC	ONTROLLED DOCUMENT.	DWN 09NOV2021 SATHISH KUMAR G CHK 09NOV2021	TE Connectivity
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± -	APPLICATION SPEC	CPC SQ. FLANGE RCPT CONNECTOR CABLE, STD SEX, SERIES 1, 23-24
	4 PLC ± - ANGLES ± -	_	SIZE CAGE CODE DRAWING NO RESTRICTED TO
MATERIAL _	FINISH _	WEIGHT	A3 00779 G- 2387127 -
		CUSTOMER DRAWING	SCALE NTS SHEET 1 OF 1 REV B

1470-19 (1/15)