NSYTBP24198T

PC box IP66 IK08 RAL7035 Int.H225W175D80 Ext.H241W194D87 Transp.cover H20





Main

Range	Thalassa
Product name	Thalassa TBP
Device Application	Multi-purpose
Category	Industrial box
Height	9.49 in (241 mm)
Width	7.64 in (194 mm)
Depth	3.43 in (87 mm)
Internal height	8.86 in (225 mm)
Internal width	6.89 in (175 mm)
Internal depth	3.15 in (80 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws
	· · · · · · · · · · · · · · · · · · ·

Complementary

Material	polycarbonate	
Color	Gray RAL 7035) Transparent	
Standards	UL 508 A IEC 62208	
Product Certifications	TÜV UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor	
Net Weight	1.41 lb(US) (0.64 kg)	

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480165849	
1	
24.62 oz (698.0 g)	
No	
HU	
	ES1 3606480165849 1 24.62 oz (698.0 g) No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.94 in (10.0 cm)
Package 1 width	7.87 in (20.0 cm)
Package 1 Length	10.04 in (25.5 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	21.56 lb(US) (9.78 kg)
Package 2 Height	15.94 in (40.5 cm)
Package 2 width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Weight	568.79 lb(US) (258.0 kg)
Package 3 Height	86.61 in (220.0 cm)
Package 3 width	39.37 in (100.0 cm)
Package 3 Length	47.24 in (120.0 cm)

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Yes
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile
End Of Life Information

Contractual warranty

Warranty 18	8 months
-------------	----------