

## N and P-Channel Enhancement Mode Power MOSFET

### Description

The RM2003 uses advanced trench technology to provide excellent  $R_{DS(ON)}$  and low gate charge . The complementary MOSFETs may be used to form a level shifted high side switch, and for a host of other applications.

### General Features

#### ● N-Channel

$V_{DS} = 20V, I_D = 3A$

$R_{DS(ON)} < 35m\Omega @ V_{GS}=4.5V$


$R_{DS(ON)} < 55m\Omega @ V_{GS}=2.5V$

#### ● P-Channel

$V_{DS} = -20V, I_D = -3A$


$R_{DS(ON)} < 75m\Omega @ V_{GS}=-4.5V$

$R_{DS(ON)} < 100m\Omega @ V_{GS}=-2.5V$




N-channel

P-channel



Marking and pin Assignment



SOT-23-6L top view

### Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
2003	RM2003	SOT-23-6L	Ø180mm	8mm	3000 units

### Absolute Maximum Ratings ( $T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	$V_{DS}$	20	-20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	$\pm 12$	V
Continuous Drain Current $T_A=25^\circ C$	$I_D$	3	-3	A
		2.4	-2.4	
Pulsed Drain Current <sup>(Note 1)</sup>	$I_{DM}$	13	-13	A
Maximum Power Dissipation	$P_D$	0.8	0.8	W
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 To 150	-55 To 150	°C

### Thermal Characteristic

Thermal Resistance,Junction-to-Ambient <sup>(Note2)</sup>	$R_{\theta JA}$	N-Ch	156	°C/W
Thermal Resistance,Junction-to-Ambient <sup>(Note2)</sup>	$R_{\theta JA}$	P-Ch	156	°C/W

## N-CH Electrical Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	20	22	-	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}}=20\text{V}, V_{\text{GS}}=0\text{V}$	-	-	1	$\mu\text{A}$
Gate-Body Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=\pm 12\text{V}, V_{\text{DS}}=0\text{V}$	-	-	$\pm 100$	nA
<b>On Characteristics</b> <sup>(Note 3)</sup>						
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	0.5	0.75	1.2	V
Drain-Source On-State Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=2.5\text{V}, I_{\text{D}}=2.8\text{A}$	-	36	55	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_{\text{D}}=3\text{A}$	-	28	35	$\text{m}\Omega$
Forward Transconductance	$g_{\text{FS}}$	$V_{\text{DS}}=5\text{V}, I_{\text{D}}=3\text{A}$	-	8	-	S
<b>Dynamic Characteristics</b> <sup>(Note 4)</sup>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}}=10\text{V}, V_{\text{GS}}=0\text{V}, F=1.0\text{MHz}$	-	260	-	PF
Output Capacitance	$C_{\text{oss}}$		-	48	-	PF
Reverse Transfer Capacitance	$C_{\text{rss}}$		-	27	-	PF
<b>Switching Characteristics</b> <sup>(Note 4)</sup>						
Turn-on Delay Time	$t_{\text{d(on)}}$	$V_{\text{DD}}=10\text{V}, R_{\text{L}}=3.3\Omega$ $V_{\text{GS}}=4.5\text{V}, R_{\text{GEN}}=6\Omega$	-	2.5	-	nS
Turn-on Rise Time	$t_r$		-	3.2	-	nS
Turn-Off Delay Time	$t_{\text{d(off)}}$		-	21	-	nS
Turn-Off Fall Time	$t_f$		-	3	-	nS
Total Gate Charge	$Q_g$	$V_{\text{DS}}=10\text{V}, I_{\text{D}}=3\text{A}, V_{\text{GS}}=4.5\text{V}$	-	2.9	5	nC
Gate-Source Charge	$Q_{\text{gs}}$		-	0.4	-	nC
Gate-Drain Charge	$Q_{\text{gd}}$		-	0.6	-	nC
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Voltage <sup>(Note 3)</sup>	$V_{\text{SD}}$	$V_{\text{GS}}=0\text{V}, I_{\text{S}}=3\text{ A}$	-	-	1.2	V
Diode Forward Current <sup>(Note 2)</sup>	$I_{\text{S}}$		-	-	3	A

### Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board,  $t \leq 10$  sec.
3. Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .
4. Guaranteed by design, not subject to production


## P-CH Electrical Characteristics (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20		-	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=-20V, V_{GS}=0V$	-	-	-1	$\mu A$
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS}=\pm 12V, V_{DS}=0V$	-	-	$\pm 100$	nA
<b>On Characteristics</b> (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.4	-0.7	-1	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=-4.5V, I_D=-2.5A$	-	60	75	$m\Omega$
		$V_{GS}=-2.5V, I_D=-2A$	-	81	100	$m\Omega$
Forward Transconductance	$g_{FS}$	$V_{DS}=-5V, I_D=-2.5A$	-	9.5	-	S
<b>Dynamic Characteristics</b> (Note 4)						
Input Capacitance	$C_{iss}$	$V_{DS}=-10V, V_{GS}=0V, F=1.0MHz$	-	325	-	PF
Output Capacitance	$C_{oss}$		-	63	-	PF
Reverse Transfer Capacitance	$C_{rss}$		-	37	-	PF
<b>Switching Characteristics</b> (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=-10V, R_L=5\Omega, V_{GS}=-4.5V, R_{GEN}=3\Omega$	-	11	-	nS
Turn-on Rise Time	$t_r$		-	5.5	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	22	-	nS
Turn-Off Fall Time	$t_f$		-	8	-	nS
Total Gate Charge	$Q_g$	$V_{DS}=-10V, I_D=-2A, V_{GS}=-4.5V$	-	3.2	-	nC
Gate-Source Charge	$Q_{gs}$		-	0.6	-	nC
Gate-Drain Charge	$Q_{gd}$		-	0.9	-	nC
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Voltage (Note 3)	$V_{SD}$	$V_{GS}=0V, I_S=-3A$	-	-	-1.2	V
Diode Forward Current (Note 2)	$I_S$		-	-	-3	A


### Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board,  $t \leq 10$  sec.
3. Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$ .
4. Guaranteed by design, not subject to production


## N- Channel Typical Electrical and Thermal Characteristics (Curves)




**Figure 1:Switching Test Circuit**




**Figure 2:Switching Waveforms**




**Figure 3 Power Dissipation**



**Figure 4 Drain Current**




**Figure 5 Output Characteristics**




**Figure 6 Drain-Source On-Resistance**


## N- Channel Typical Electrical and Thermal Characteristics (Curves)




**Figure 7 Transfer Characteristics**




**Figure 8 Drain-Source On-Resistance**




**Figure 9  $R_{DS(on)}$  vs  $V_{GS}$**



**Figure 10 Capacitance vs  $V_{DS}$**




**Figure 11 Gate Charge**




**Figure 12 Source- Drain Diode Forward**

## N- Channel Typical Electrical and Thermal Characteristics (Curves)




**Figure 13 Safe Operation Area**




**Figure 14 Normalized Maximum Transient Thermal Impedance**


## P- Channel Typical Electrical and Thermal Characteristics (Curves)




**Figure 1:Switching Test Circuit**




**Figure 2:Switching Waveforms**




**Figure 3 Power Dissipation**



**Figure 4 Drain Current**



**Figure 5 Output Characteristics**



**Figure 6 Drain-Source On-Resistance**

## P- Channel Typical Electrical and Thermal Characteristics (Curves)




Figure 7 Transfer Characteristics




Figure 8 Drain-Source On-Resistance




Figure 9  $R_{DS(on)}$  vs  $V_{GS}$




Figure 10 Capacitance vs  $V_{DS}$




Figure 11 Gate Charge






Figure 12 Source- Drain Diode Forward

## P- Channel Typical Electrical and Thermal Characteristics (Curves)




**Figure 13 Safe Operation Area**



**Figure 14 Normalized Maximum Transient Thermal Impedance**

## SOT23-6L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

<b>Package</b>	Tube (pcs/tube)	Tube (pcs/inner box)	Tube (pcs/cartoon)	Tape&Reel (pcs/reel)	Tape&Reel (pcs/inner box)	Tape&Reel (pcs/cartoon)
DFN5x6/DFN3x3	100	10,000	100,000	2,500	5,000	40,000
DFN1006	—	—	—	10,000	10,000	400,000
SOP-8	100	10,000	100,000	4,000	4,000	20,000
TSSOP-8	100	32,000	128,000	3,000	6,000	48,000
SOT-23-3L	—	—	—	3,000	30,000	120,000
SOT-23-6L	—	—	—	3,000	30,000	120,000
SOT-23(6R)	—	—	—	3,000	30,000	120,000
SOT-363	—	—	—	3,000	30,000	120,000
SOT-523	—	—	—	3,000	30,000	120,000
<b>SOT223</b>	—	—	—	<b>2,500</b>	<b>2,500</b>	<b>20,000</b>
TO-220	50	1,000	5,000	—	—	—
TO-220F	50	1,000	10,000	—	—	—
TO-247	30	300	1,200	—	—	—
TO-251	80	4,000	40,000	—	—	—
TO-251S(4R)	80	4,000	40,000	—	—	—
TO-252-2L(4R)	80	4,000	40,000	2,500	2,500	25,000
TO-263-2L	50	1,000	10,000	800	800	8,000
TO-3P	30	300	3,000	—	—	—
TO-92	—	—	—	1,000(袋装)	10,000	100,000

## **DISCLAIMER NOTICE**

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.