


NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:


SHELL: ZINC ALLOY, NICKEL PLATED. INSERT: THERMOPLASTIC, UL94 V-0. NUTS: AL ALLOY NICKEL PLATED. SEAL GASKET: NBR/SILICONE RUBBER.

O-RING: NBR/SILICONE RUBBER.

- 2. SPECIFICATIONS:
 - 2.1 RATED CURRENT: 13A (MAX).
 - 2.2 RATED VOLTAGE: 500V(AC/DC).
 - 2.3 OPERATING TEMPERATURE: SEE CHART.
 - 2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE@2000 VOLTS AC.
 - 2.5 INSULATION RESISTANCE: 5000 MEGOHMS MIN.
 - 2.6 IP--CLASS: IP67 (MATED CONNECTOR).
 - 2.7 MATING CYCLES DURABILITY: 500 CYCLES MIN.
 - 2.8 RoHS COMPLIANT.
- 3. SUITABLE CONTACTS: 16# CONTACTS.
- 4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



PANEL CUT OUT REFERENCE



KEY POS	PART NUMBER			1		
	-40°C ~ 105°C	-40°C ~ 125°C	Α	В	С	D
N	RT07147SNH	RT07147SNH03	105°	140°	215°	265°
W	RT07147SWH	RT07147SWH03	60°	140°	215°	265°
Х	RT07147SXH	RT07147SXH03	105°	160°	215°	265°
Υ	RT07147SYH	RT07147SYH03	105°	140°	225°	265°
Z	RT07147SZH	RT07147SZH03	105°	140°	215°	295°

QUANTITY	PART NUMBER		DESCRIPTION				ITEM
		MA	TERL	ALS LI	ST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions +1/64		SIGNATURE	ES DATE	Amphenol			
		DRAWN: Flan	May-19-21	Amphenoi			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED: Blink	May-20-21	Sine Systems - www.amphenol-sine.com			
PROCESS SPECIFICATIONS: INFORMATION ONLY. DESI SPECIFICATIONS AND PER SHOWN HEREON ARE THE THE AMPHENOL CORPORA		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL: Tommy	May-20-21	- Cilitari Formanip, ini 10000			
		CUSTOMER:		ECOMATE RM,RECEPTACLE, JAM NUT,SIZE 14,7POS,SOCKET.			
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS AGE SIR IS CETT TO NORMA					
				B C-	RT071479		A1
		TIONS.	SCALE: NONE		SHEET 1 OF	1	

RT07147S*Hx REV:

E∞Mate RM,RECEPTACLE,JAM NUT,SIZE 14,7 POS,SOCKET.

EV: **A1** SH: 1 OF