



SS Stainless Steel

3 Type

- C** With plain blind bore, tol. H7
- E** With tapped blind bore
- D** With tapped through bore

Inch table

Dimensions in: inches - millimeters

1 d_1	2 d_2 Thread Type E / Type D		2 $d_3 + 0.001$ Bore Type C		d_4	h	k	t min.
.75 19.1	10 x 24	1/4 x 20	B 3/16	B 1/4	.50 12.7	.63 16.0	.25 6.4	.38 9.7
1.00 25.4	1/4 x 20	5/16 x 18	B 1/4	B 5/16	.63 16.0	.75 19.1	.25 6.4	.50 12.7
1.50 38.1	5/16 x 18	3/8 x 16	B 5/16	B 3/8	.75 19.1	1.00 25.4	.31 7.9	.63 16.0
2.00 50.8	3/8 x 16	1/2 x 13	B 3/8	B 1/2	1.00 25.4	1.13 28.7	.38 9.7	.63 16.0
2.50 63.5	1/2 x 13	5/8 x 11	B 1/2	B 5/8	1.50 38.1	1.50 38.1	.56 14.2	.75 19.1
3.00 76.2	5/8 x 11	3/4 x 10	B 5/8	B 3/4	1.75 44.5	1.75 44.5	.63 16.0	1.00 25.4

Specification

- Stainless steel **NI**
European Standard No. 1.4305 (AISI 303)
- Steel, blackened finish **ST**
- Machined from solid bar
- Knurled head for non-slip grip
- RoHS compliant

Information

KRSK knurled nuts are used for applications which require higher durability than plastic or aluminum, yet appearance is essential.

see also...

- Knurled Screws KRSK (with Threaded Stud)

How to order	
1	Handle diameter d_1
2	Bore d_3 (Thread d_2)
3	Type
4	Material

1 2 3 4
KRSK-1.00-B5/16-C-NI

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

