

3 PRODUCT NO. PCB THICKNESS DIMENSION "A" CONTACT GOLD THICKNESS 10040812-001LF 1.57±0.10 2.50±0.10 30 u"/0.76 um

- V -1.27 TYP 2.54 Ø2.50±0.05-0.97 3.65 0 0 0 0 0 0 0 0 0 0 0 0 0 0 - U -0 3.81 TYP 2.54 Ø0.50 TYP Ø1.90±0.05 ⊕ 0.05 U V POS. 32--POS. I ⊕ 0.05 U

> RECOMMENDED PCB LAYOUT SCALE 2:1

> > NOTE: -

I. MATERIAL:

HOUSING - HIGH TEMPERATURE PLASTIC, BLACK OR GRAY

- COPPER ALLOY CONTACT BOARD LOCK - COPPER ALLOY

2. FINISH:

2. FINISH:

ALL CONTACTS AND BOARD LOCKS

NICKEL UNDERPLATE OVERALL,

TIN (LEAD-FREE) ON SOLDER TAILS,

GOLD ON CONTACT AREAS

3. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

4. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFIOW OVEN OR VAPOR PHASE REFLOW OVEN

• + +	4 LANE RECEPTACLE VERTICAL P/F ASSY	dwg no	100408		Rev.
catalog no			CUSTOMER	sheet 2 of	2

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous que que time que ec soit sans autorisation ecrite du propietaire. Propriéte de c FCI. Droits de reproduction FCI.

PDM: Rev:A

STATUS: Released 4 Printed: Jan 06, 2006

В

C.

D