

RH210 Compact Hygro-Thermometer



Compact handheld Hygro-Thermometer with large dual LCD displays Temperature and Humidity or Dew Point simultaneously. Dew Point measurement can indicate if conditions are suitable for painting. Ideal for many industrial applications or home use.

Applications: - Water Restoration

- Factories - Clean rooms
- Offices
- Storage facilities
- Greenhouses
- Painting - HVAC



Features

- Compact design features large dual display of Temperature and Humidity or Dew Point
- Uses precision capacitance sensor
- Min/Max function stores & recalls highest
 and lowest readings
- Data Hold function freezes reading on display

- Auto Power Off with disable feature
- Low battery indication
- Complete with probe and 39" (1m) cable, 9V battery, and soft case

Specifications	Range	Max Resolution	Basic Accuracy
Humidity	10% to 95%RH	0.1%RH	±3%RH
Temperature	32 to 122°F (0 to 50°C)	0.1°	±1.5°F (±0.8°C)
Dew Point	-13.5 to 120.0°F (-25.3 to 48.9°C)	0.1°	±2.2°F (±1.2°C)
Dimensions	5.3 x 2.4 x 1.3" (135 x 60 x 33mm)		
Weight	9.3oz. (264g)		

Ordering

RH210..... Hygro-Thermometer

