




- > Stainless steel offers corrosion resistance
- > 80% anti-magnetic (20% magnetic due to weld during manufacturing)
- > Blunt tips offer a firm grip but won't damage surrounding components
- > 92 37 64, 92 47 01 and 92 67 63 are 1000V insulated
- > ESD handle versions discharge electrostatic energy through the handles in a gradual and controlled manner
- > 92 94 91, 92 95 89 and 92 95 90 have a cross over design
- > 92 58 74 ESD and 92 78 77 ESD (Dissipative $10^4/10^9$ OHM regarding DIN EN 61340-5-1)




92 37 64




92 47 01




92 61 01, 92 61 02, 92 64 43,
92 72 45 and 92 78 77 ESD




92 94 91




92 67 63




92 95 89



95 52 23 and 92 58 74 ESD



92 84 18



92 95 90

	Product Number	Length	Width	Height	Finish	Style	Gripping Surface	Tip (A)	Tip (B)
	92 37 64	6"	9/16"	1 9/16"	stainless steel, 80% anti-magnetic, acid resistant, 1000V VDE	30° angled	serrated	1.00 mm	1.30 mm
	92 47 01	5 3/4"	5/8"	1 1/2"	stainless steel, 80% anti-magnetic, acid resistant, 1000V VDE	30° angled	serrated	1.30 mm	3.00 mm
	92 52 23	4 5/8"	3/8"	3/8"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.30 mm	2.00 mm
	92 58 74 ESD	4 5/8"	3/8"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.30 mm	2.00 mm
	92 61 01	7 7/8"	1/2"	13/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	2.00 mm	3.20 mm
	92 61 02	11 3/4"	9/16"	7/8"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	2.50 mm	4.70 mm
	92 64 43	4 3/4"	3/8"	9/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	1.20 mm	2.70 mm
	92 67 63	5 3/4"	7/16"	1 1/2"	stainless steel, 80% anti-magnetic, acid resistant, 1000V VDE	straight	serrated	1.30 mm	3.00 mm
	92 72 45	5 3/4"	7/16"	9/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	1.30 mm	2.70 mm
	92 78 77 ESD	5 3/4"	7/16"	11/16"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	serrated	1.30 mm	2.70 mm
	92 84 18	5"	7/16"	11/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	0.50 mm	1.00 mm
	92 94 91	6 1/4"	7/16"	1/2"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	1.30 mm	4.50 mm
	92 95 89	6 1/2"	7/16"	13/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	0.80 mm	1.00 mm
	92 95 90	6 3/8"	7/16"	13/16"	stainless steel, 80% anti-magnetic, acid resistant	40° angled	serrated	0.80 mm	1.00 mm