GENERAL VIEWS

.287 [7.29]

.260 [6.6]

. 045

[1.14]


.040 [1.02]

.020 [0.51]

.040 TYP -

[1.02]

RoHS



DO NOT SCALE DRAWING DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE

PLUG HOUSING

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED. OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATENTS MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE VISIT: HTTP://BELFUSE.COM/STEWART/STEWART\_PATENTS/

JC JC CT370038

6-4-01

DATE 5 - 30 - 0 |

TITLE: UNSHIELDED CAT 5E PLUG

CONNECTOR a bel group

IIII8 Susquehanna Trail South Glen Rock, PA 17327-9199 (717) 235-7512 http://www.stewartconnector.com

CONTACT PLATING PART NUMBER IN MATING AREA THIRD ANGLE PROJECTION

SS-37000-003 BAG OF 25 50 MICRO-INCHES [1.27um] BULK 50 MICRO-INCHES [1.27um] SS-37000-001 PACKAGE

Pro/E

.460 [11.68] -WIRE GUIDE SURFACES [3.15] .240 [6.1]



4- PLUG SPECIFICATION: PR026-01

/6ackslash TERMINATED PLUG HEIGHT: .237 [6.02]  $\pm$ .005 [0.13]

5- DIMENSIONS AND TOLERANCES COMPLY WITH TIA-1096 STANDARD.

3- CONTACTS TERMINATE SOLID OR STRANDED CONDUCTORS BETWEEN .037 [0.94] TO .042 [1.07] OUTSIDE DIAMETER OF INSULATION.

FRONT HOUSING PLASTIC: CLEAR POLYCARBONATE, UL 94-VO CONTACTS: PHOSPHOR BRONZE, SELECTIVE GOLD PLATING

TRM 3-23-16 B 4 10632 7-27-16 В5 10728 TRM

- .845 [21.46]

- .885 [22.48]

[5.94]

[15.8]

TO END OF LATCH TAB

.019 TYP [0.49]

.312 [7.92]

DATE APP'D BY