

CLL3595

**SURFACE MOUNT
LOW LEAKAGE SILICON DIODE**



SOD-80 CASE



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CLL3595 type is an epitaxial planar silicon diode, manufactured in a hermetically sealed glass surface mount package, designed for low leakage, high conductance applications.

MARKING: CATHODE BAND

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)

Peak Repetitive Reverse Voltage	V_{RRM}	150	V
Peak Working Reverse Voltage	V_{RWM}	125	V
Average Forward Current	I_O	150	mA
Forward Steady-State Current	I_F	225	mA
Recurrent Peak Forward Current	I_f	600	mA
Peak Forward Surge Current (1.0s pulse)	I_{FSM}	500	mA
Peak Forward Surge Current (1.0 μ s pulse)	I_{FSM}	4.0	A
Power Dissipation	P_D	500	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +200	$^\circ\text{C}$
Thermal Resistance	Θ_{JA}	350	$^\circ\text{C/W}$

SYMBOL		UNITS
V_{RRM}	150	V
V_{RWM}	125	V
I_O	150	mA
I_F	225	mA
I_f	600	mA
I_{FSM}	500	mA
I_{FSM}	4.0	A
P_D	500	mW
T_J, T_{stg}	-65 to +200	$^\circ\text{C}$
Θ_{JA}	350	$^\circ\text{C/W}$


ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_R	$V_R=125\text{V}$		1.0	nA
I_R	$V_R=125\text{V}, T_A=125^\circ\text{C}$		500	nA
I_R	$V_R=125\text{V}, T_A=150^\circ\text{C}$		3.0	μA
I_R	$V_R=30\text{V}, T_A=125^\circ\text{C}$		300	nA
BV_R	$I_R=100\mu\text{A}$	150		V
V_F	$I_F=1.0\text{mA}$	0.54	0.69	V
V_F	$I_F=5.0\text{mA}$	0.62	0.77	V
V_F	$I_F=10\text{mA}$	0.65	0.80	V
V_F	$I_F=50\text{mA}$	0.75	0.88	V
V_F	$I_F=100\text{mA}$	0.79	0.92	V
V_F	$I_F=200\text{mA}$	0.834	1.00	V
C_T	$V_R=0, f=1.0\text{MHz}$		8.0	pF
t_{rr}	$V_R=3.5\text{V}, I_f=10\text{mA}, R_L=1.0\text{k}\Omega$		3.0	μs

CLL3595
 SURFACE MOUNT
 LOW LEAKAGE SILICON DIODE



SOD-80 CASE - MECHANICAL OUTLINE



MARKING: CATHODE BAND

DIMENSIONS				
SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.130	0.146	3.30	3.71
B	0.014		0.35	
C (DIA)	0.049	0.067	1.25	1.70

SOD-80 (REV:R2)

R4 (8-January 2010)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms



<http://www.centrasemi.com>

Product End of Life Notification

PDN ID:	PDN01111
Notification Date:	1/18/19
Last Buy Date:	7/18/19
Last Shipment Date	1/18/20

Summary: The CLL3595 Low Leakage Diode is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

<u>Central Part Number</u>	<u>Replacement</u>
CLL3595 BK	CMHD3595 BK
CLL3595 TR	CMHD3595 TR

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centrasemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.