TMC2PACK01

Analogue input number

Analogue input cartridge, Modicon M221, packaging 2 analog inputs, I/O extension





Main Range of Product Modicon M221 Product or Component Type Product Specific Packaging Application Product Compatibility Modicon M221C

Complementary

Analogue input type	Current 420 mA Current 020 mA Voltage 010 V
Analogue input resolution	12 bits
LSB value	2.44 mV 010 V voltage 4.88 μA 020 mA current 3.91 μA 420 mA current
Conversion time	20 ms
Sampling duration	10 ms
Absolute accuracy error	+/- 0.1 % of full scale 77 °F (25 °C) +/- 1 % of full scale
Temperature Drift	+/- 0.02 %FS/°C
Repeat accuracy	+/- 0.5 %FS
Non-linearity	+/- 0.01 %FS
Cross talk	<= 1 LSB
Type of Cable	Twisted shielded pairs cable
Electrical connection	3 x 1.5 mm² 2 screw terminal blocks pitch 3.81 mm for inputs
Maximum cable distance between devices	Twisted shielded pairs cable <98.43 ft (30 m) input
Insulation	Non-insulated between analogue input and internal logic
Height	1.61 in (41 mm)
Depth	0.59 in (15 mm)
Width	1.38 in (35 mm)
Net Weight	0.03 lb(US) (0.015 kg)
Permissible continuous overload	13 V voltage 40 mA current
Input impedance	<= 250 Ohm current >= 1 MOhm voltage

Environment

ZIIVII OIIIII OIII		
Immunity to microbreaks	10 ms	

Ordering and shipping details

Category	22533-M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	3606480649134
Nbr. of units in pkg.	1
Package weight(Lbs)	0.71 oz (20.0 g)
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.38 in (3.5 cm)
Package 1 width	1.81 in (4.6 cm)
Package 1 Length	2.76 in (7 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Weight	7.29 lb(US) (3.305 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	€ End Of Life Information	
PVC free	Yes	