8501XO20XLV02

NEMA Control Relay, Type X, latching, 10A resistive at 600 VAC, 2 normally open contacts, 110/120 VAC 50/60 Hz coil





Main

Range	8501X
Relay Type	Latching
Product	Relay
Current Rating	10 A AC 5 A DC
Contact Configuration	2 NO 2 standard contact cartridges
Number of Poles	2P
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Voltage Rating	600 V AC
Mounting Type	Panel
Operating Temperature	-40160 °F (-4071 °C)
Electrical Connection	Screw clamp terminals
Certifications	CE UL Listed CSA
Operating Time	15 ms - pick-up 13 ms - drop-out
Height	3.50 in (88.90 mm)
Width	2.23 in (56.64 mm)
Depth	6.54 in (166.12 mm)

Ordering and shipping details

Category	21158-8501 XO (AC)	
Discount Schedule	CP2	
GTIN	785901028499	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.91 lb(US) (1.32 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	21.59 in (54.839 cm)	
Package 1 width	8.50 in (21.59 cm)	
Package 1 Length	54.84 in (139.29 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	252	
Package 2 Weight	733.98 lb(US) (332.927 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	36.00 in (91.44 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Contractual warranty

	,
Warranty	18 months