

# CJ-series Position Control Unit with MECHATROLINK-II interface

# CJ1W-NC□71

CSM\_CJ1W-NC\_71\_DS\_E\_9\_4

## Decrease TCO with Simple Operation, Reduced Wiring, Batch Settings, and Batch Management

- Control Servos for up to 16 axes in a motion network with one Position Control Unit that supports MECHATROLINK-II \*.
- \* MECHATROLINK-II is a registered trademark of the MECHATROLINK Members Association.




CJ1W-NC71

## Features

- **Even Smaller**  
Positioning of up to 16 axes can be controlled with a body the size of one CJ-series Unit.  
The compact body provides a perfect fit to meet the need for downsizing of equipment for multi-axis control.
- **Single-cable Connection with Flexible Wiring Placement**  
With MECHATROLINK-II, connecting to the Servo Drive is easy. Just use a single cable (2-core shielded twisted-pair cable). Reduced wiring, with a total cable length of 50 m (or 30 m for 16 axes), allows more freedom in constructing systems.
- **Less Time Spent on Startup and Maintenance**  
Servo parameters can be set from the PLC.  
This means that settings and adjustments can be performed from one location rather than having to connect to each Servo Drive separately.
- **Simple Expansion**  
An easily expandable system can be constructed that is just as efficient now with a few axes or later with up to 16 axes.
- **Linked Operation of Multiple Axes with MA Functionality**  
The addition of an Interpolation Compensation Axis Stop Mode Setting and Interaxial Allowance Deviation Setting to linear interpolation compensation enables easier setting of linked operation between axes.

# System Configuration



## Ordering Information

### International Standards

- The standards are abbreviated as follows: U: UL, U1: UL(Class I Division 2 Products for Hazardous Locations), C: CSA, UC: cULus, UC1: cULus (Class I Division 2 Products for Hazardous Locations), CU: cUL, N: NK, L: Lloyd, and CE: EC Directives.
- Contact your OMRON representative for further details and applicable conditions for these standards.

### CJ-series Units

Unit type	Product name	Specifications		No. of unit numbers allocated	Current consumption (A)		Model	Standards
		Control output interface	No. of axes		5 V	24 V		
CJ1 CPU Bus Units	Position Control Unit with MECHATROLINK-II interface 	Control commands executed by MECHATROLINK-II synchronous communications. Direct operation by ladder programming. Control mode: Position control, speed control, or torque control	2	1	0.36	-	CJ1W-NC271	UC1, CE
			4				CJ1W-NC471	
			16				CJ1W-NCF71	
			16				CJ1W-NCF71-MA	

**Note:** This unit cannot be used with the Machine Automation Controller NJ-series.

### Support Software

Product name	Specifications	Number of licenses	Media	Model	Standards
FA Integrated Tool Package CX-One Ver. 4.□	The CX-One is a comprehensive software package that integrates Support Software for OMRON PLCs and components. CX-One runs on the following OS. OS: Windows XP (Service Pack 3 or higher, 32-bit version) / Windows Vista (32-bit/64-bit version) / Windows 7 (32-bit/64-bit version) / Windows 8 (32-bit/64-bit version) / Windows 8.1 (32-bit/64-bit version) / Windows 10 (32-bit/64-bit version)  CX-One Ver. 4.□ includes CX-Motion-NCF Ver. 1.□. For details, refer to the CX-One catalog (Cat. No. R134).	1 license*	DVD	CXONE-AL01D-V4	-

\* Multi licenses (3, 10, 30, or 50 licenses) and DVD media without licenses are also available for the CX-One.

### MECHATROLINK-related Devices and Cables (Manufactured by Yaskawa Corporation)

Name	OMRON model number	Yaskawa model number
MECHATROLINK-II Cables (with ring core and USB connector on both ends)	0.5 m	FNY-W6003-A5
	1.0 m	FNY-W6003-01
	3.0 m	FNY-W6003-03
	5.0 m	FNY-W6003-05
	10.0 m	FNY-W6003-10
	20.0 m	FNY-W6003-20
30.0 m	FNY-W6003-30	JEPMC-W6003-30
MECHATROLINK-II Terminating Resistor	Terminating resistance	FNY-W6022
MECHATROLINK-II Repeater	Communications Repeater	---
		JEPMC-REP2000-E

**Note:** MECHATROLINK-related Devices and Cables are manufactured by Yaskawa Corporation, but they can be ordered directly from OMRON using the OMRON model numbers. (Yaskawa-brand products will be delivered even when they are ordered from OMRON.)

### Accessories

None

## Mountable Racks

Model	NJ system		CJ system (CJ1, CJ2)		CP1H system	NSJ system	
	CPU Rack	Expansion Rack	CPU Rack	Expansion Backplane	CP1H PLC	NSJ Controller	Expansion Backplane
CJ1W-NC□71 (-MA)	Not Supported		16 Units max. (10 per Rack)		2 Units *	Not supported	10 Units

\* A CP1W-EXT01 CJ Unit Adaptor is required.

# Specifications

## General Specifications

Item	Specifications
Model	CJ1W-NC271/471/F71 (-MA)
Internal current consumption	360 mA max. at 5 V DC
Dimensions	31 × 90 × 65 mm (W × H × D)
Weight	95 g max.
Ambient operating temperature	0 to 55°C
Approved standards	CE, cULus, and C-tick

Specifications not listed above conform to general CJ Series specifications.

## Functions and Specifications

Item	Specifications	
Unit classification	CPU Bus Unit	
Applicable PLCs	CJ Series	
Possible unit number settings	0 to F	
I/O allocations	<b>Common Operating Memory Area</b>	Words allocated in CPU Bus Unit Area: 25 words (15 output words, 10 input words)
	<b>Axis Operating Memory Area</b>	Allocated in one of the following areas (user-specified): CIO, Work, Auxiliary, Holding, DM, or EM Area. Number of words allocated: 50 words (25 output words, 25 input words) × Highest axis No. used
Compatible devices	<ul style="list-style-type: none"> <li>• OMRON G5-series Servo Drives (Built-in MECHATROLINK-II communications)</li> <li>• OMRON G-series Servo Drives (Built-in MECHATROLINK-II communications)</li> </ul>	
Control method	Control commands executed using MECHATROLINK-II synchronous communications.	
Maximum number of controlled axes	CJ1W-NC271: 2 axes, CJ1W-NC471: 4 axes, CJ1W-NC71: 16 axes	
Control units	<b>Position command unit</b>	Command unit: Depends on the Electronic Gear Setting in the Servo Parameters. Default setting: Pulses
	<b>Speed command unit for position control</b>	Command units/s
	<b>Acceleration/deceleration speeds for position control</b>	10,000 command units/s <sup>2</sup>
	<b>Speed command unit for speed control</b>	0.001% of the motor's momentary maximum rotation speed
	<b>Torque command unit for torque control</b>	0.001% of the motor's momentary maximum torque
Control command range	<b>Position command range</b>	-2,147,483,648 to 2,147,483,647 (command units)
	<b>Speed command range for position control</b>	0 to 2,147,483,647 (command units/s)
	<b>Acceleration/deceleration speeds for position control</b>	1 to 65,535 (10,000 command units/s <sup>2</sup> )
	<b>Speed command range for speed control</b>	-199.999% to 199.999% The upper limit of the speed command range depends on the specifications of the Servo Drive.
	<b>Torque command range for torque control</b>	-199.999% to 199.999% The upper limit of the torque command range depends on the specifications of the Servo Drive.
Control functions	<b>Servo lock/unlock</b>	Creates (Servo lock) or releases (Servo unlock) the position loop on the PCU.
	<b>Position control</b>	Positions to an absolute position or relative position according to the target position and target speed specified from the ladder program.
	<b>Origin determination</b>	<ul style="list-style-type: none"> <li>• Origin search: Establishes the origin using the specified search method.</li> <li>• Present position preset: Changes the present position to a specified position to establish the origin.</li> <li>• Origin return: Returns the axis from any position to the established origin.</li> <li>• Absolute encoder origin: Establishes the origin using a Servomotor that has an absolute encoder, without having to use an origin search.</li> </ul>
	<b>Jogging</b>	Outputs pulses at a fixed speed in the forward rotation or reverse rotation direction.
	<b>Interrupt feeding</b>	Performs positioning by moving the axis a fixed amount when an external interrupt input is received while the axis is moving.
	<b>Speed control</b>	Performs speed control by sending a command to the Servo Drive speed loop.
	<b>Torque control</b>	Performs torque control by sending a command to the Servo Drive current loop.
	<b>Stop functions</b>	<ul style="list-style-type: none"> <li>• Deceleration stop: Decelerates the moving axis to a stop.</li> <li>• Emergency stop: Positions the moving axis for the number of pulses remaining in the deviation counter and then stops the axis.</li> </ul>

Item		Specifications
Auxiliary functions	Acceleration/deceleration curves	Sets one of the following: a trapezoidal (linear) curve, an exponential curve, or an S-curve (moving average).
	Torque limit	Restricts the output torque during axis operation.
	Override	Multiplies the axis command speed by a specified ratio. Override: 0.01% to 327.67%
	Servo parameter transfer	Reads and writes the Servo Drive parameters from the ladder program in the CPU Unit.
	Monitoring function	Monitors the control status of the Servo Drive, such as the command coordinate positions, feedback position, current speed, and torque.
	Software limits	Limits software operation within the positioning range during position control.
	Backlash compensation	Compensates for the amount of play in the mechanical system according to a set value.
	Deviation counter reset	The position deviation in the Servo Drive's deviation counter can be reset to 0 (unit version 1.3 or later).
External I/O	Position Control Unit	One MECHATROLINK-II interface port
	Servo Drive I/O	Forward/reverse rotation limit inputs, origin proximity inputs, external interrupt inputs 1 to 3 (can be used as external origin inputs)
Self-diagnostic functions		Watchdog, flash memory check, memory corruption check
Error detection functions		Overtravel, Servo Drive alarm detection, CPU error, MECHATROLINK communications error, Unit setting error

## MECHATROLINK Specifications

Item	Specifications
Communications protocol	MECHATROLINK-II
Baud rate	10 Mbps
Maximum transmission distance	50 m *1
Minimum distance between stations	0.5 m
Transmission media	Shielded, twisted-pair cables
Maximum No. of stations	30 slave stations max. *2
Topology	Bus
Transfer cycle	250 μs to 8 ms
Communications method	Master-slave, totally synchronous
Encoding	Manchester encoding
Data length	17 bytes/32 bytes selectable *3


\*1. This distance is the total length of the cable connected between devices. However, the maximum length depends on the number of devices connected and whether Repeaters are used.

\*2. Up to 16 devices can be connected to the CJ1W-NCF71 (-MA), up to 2 devices can be connected to the CJ1W-NC271, and up to 4 devices can be connected to the CJ1W-NC471.

\*3. The PCU data length is fixed at 32 bytes.

## External Interface

### CJ1W-NC□71 (-MA)



### LED Indicators

LED	Name	Color	Status	Details
RUN	Run	Green	Lit	The PCU is operating normally.
			Not lit	Other condition
ERC	Unit Error	Red	Lit	A fatal error has occurred in the PCU and operation cannot continue.
			Flashing	A non-fatal error has occurred in the PCU and operation can continue.
			Not lit	Other condition
ERH	CPU Unit Error	Red	Lit	An error has occurred in the PLC.
			Not lit	Other condition
ERM	MECHATROLINK Device Error	Red	Lit	An error has occurred in MECHATROLINK communications.
			Flashing	An error has occurred in a connected MECHATROLINK device.
			Not lit	Other condition
MLK	MECHATROLINK Communications Status	Yellow	Lit	MECHATROLINK communications in progress
			Not lit	MECHATROLINK communications stopped


## Functions Supported According to Position Control Unit Versions

Model	CJ1W-NC□71 (-MA)					
	Unit Ver. 1.0	Unit Ver. 1.1	Unit Ver. 1.2	Unit Ver. 1.3	Unit Ver. 2.0	Unit Ver. 2.1
Linear interpolation	–	Supported.	Supported.	Supported.	Supported.	Supported.
Absolute encoder setup function	–	–	Supported.	Supported.	Supported.	Supported.
Deviation counter reset	–	–	–	Supported.	Supported.	Supported.
Establishing connections even when there are unconnected axes or axes with alarms that cannot be cleared	–	–	–	Supported.	Supported.	Supported.
Transferring servo parameters even when there is an axis error	–	–	–	Supported.	Supported.	Supported.
Creating servo locks during software limit detection when an absolute encoder is used	–	–	–	Supported.	Supported.	Supported.
Driver main circuit OFF error detection only when the servo is locked	–	–	–	Supported.	Supported.	Supported.
Using Holding Area address H512 and onwards for function block address allocations	–	–	–	Supported.	Supported.	Supported.
Addition of rejoin function	–	–	–	–	Supported.	Supported.
Eliminating connection restriction when Servo Drive alarms occur (enabling connection when alarm A.C90 occurs)	–	–	–	–	Supported.	Supported.
Addition of origin search operation modes	–	–	–	–	Supported.	Supported.
Addition of origin search preset function	–	–	–	–	Supported.	Supported.
Faster setting for transfer cycle and communications cycle when setting the absolute encoder PG zero point position offset with an origin search	–	–	–	–	–	Supported.

## Dimensions

(Unit: mm)

CJ1W-NC271  
CJ1W-NC471  
CJ1W-NCF71  
CJ1W-NCF71-MA



## Related Manuals

English Cat.No.	Japanese Cat.No.	Model	Name
W426	SBCE-323	CS1W-NC□71/ CJ1W-NC□71(-MA)	CS1W/CJ1W-NC□71(-MA) CS/CJ-series MECHATROLINK-II-compatible Position Control Unit User's Manual
W436	SBCE-328	CXONE-AL□□D-V□	CX-Motion-NCF Operation Manual
–	SBCE-055	CS1W-NCF71/CJ1W-NCF71	CS1W-NCF71/CJ1W-NCF71 Position Control Unit(ONNUC G-series)Technical Guide

## Terms and Conditions Agreement

### Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

### Warranties.

(a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.

(b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

### Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

### Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

### Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

### Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

### Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

### Errors and Omissions.

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.